

**Short-circuit protective breaker, Iu 0.16 A, Irm 2.5 A, Screw terminals,
Also suitable for motors with efficiency class IE3.**

Part no. PKM0-0,16
Catalog No. 072720
Alternate Catalog No. XTPMP16BNL

Delivery program

Product range				PKM0 motor protective circuit-breakers up to 32 A
Basic function				Short-circuit protective device only
Notes				Also suitable for motors with efficiency class IE3.
Connection technique				Screw terminals
Max. motor rating				
AC-3				
660 V 690 V	P	kW		0.06
Rated uninterrupted current	I _u	A		0.16
Setting range				
short-circuit release				
				
max.	I _{rm}	A		2.5
<p>Notes An appropriate overload relay must be fitted to protect motors against overload. Can be snapped on to IEC/EN 60715 top-hat rail with 7.5 or 15 mm height. Refer to catalog CA034001DE for the allocation of short circuit protection and contactor When using the PKM0 as short-circuit protection for motors with heavy starting duty, the rated operational current I_e must be over-dimensioned during engineering with the following factors:</p> <p>CLASS 5: 1,0 CLASS 10: 1,0 CLASS 15: 1,22 CLASS 20: 1,41 CLASS 25: 1,58 CLASS 30: 1,73 CLASS 35: 1,89 CLASS 40: 2,0</p>				

Technical data

General				
Standards				IEC/EN 60947, VDE 0660
Climatic proofing				Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Ambient temperature				
Storage		°C		- 40 - 80
Open		°C		-25 - +55
Enclosed		°C		- 25 - 40
Direction of incoming supply				as required
Degree of protection				
Device				IP20
Terminations				IP00
Protection against direct contact when actuated from front (EN 50274)				Finger and back-of-hand proof
Mechanical shock resistance half-sinusoidal shock 10 ms to IEC 60068-2-27		g		25
Altitude		m		Max. 2000
Terminal capacity main cable				
Screw terminals				
Solid		mm ²		1 x (1 - 6) 2 x (1 - 6)
Flexible with ferrule to DIN 46228		mm ²		1 x (1 - 6) 2 x (1 - 6)
Solid or stranded		AWG		18 - 10
Stripping length		mm		10
Specified tightening torque for terminal screws				

Main cable	Nm	1.7
Control circuit cables	Nm	1
Main conducting paths		
Rated impulse withstand voltage	U_{imp}	V AC 6000
Overvoltage category/pollution degree		III/3
Rated operational voltage	U_e	V AC 690
Rated uninterrupted current = rated operational current	$I_u = I_e$	A 0.16
Rated frequency	f	Hz 50/60
Current heat loss (3 pole at operating temperature)		W 5.39
Impedance per pole		m Ω 68000
Lifespan, mechanical	Operations	$\times 10^6$ 0.1
Lifespan, electrical (AC-3 at 400 V)		
Lifespan, electrical	Operations	$\times 10^6$ 0.1
Max. operating frequency		Ops/h 40
Motor switching capacity		
AC-3 (up to 690V)	A	0.16
DC-5 (up to 250V)	A	0.16 (3 contacts in series)
Trip blocks		
Temperature compensation		
to IEC/EN 60947, VDE 0660	$^{\circ}\text{C}$	- 5 ... 40
Operating range	$^{\circ}\text{C}$	- 25 ... 55
Temperature compensation residual error for $T > 40^{\circ}\text{C}$		$\leq 0.25\%/\text{K}$
short-circuit release		Basic device, fixed: $15.5 \times I_u$
Short-circuit release tolerance		$\pm 20\%$

Design verification as per IEC/EN 61439

Technical data for design verification		
Rated operational current for specified heat dissipation	I_n	A 0.16
Heat dissipation per pole, current-dependent	P_{vid}	W 1.8
Equipment heat dissipation, current-dependent	P_{vid}	W 5.39
Static heat dissipation, non-current-dependent	P_{vs}	W 0
Heat dissipation capacity	P_{diss}	W 0
Operating ambient temperature min.		$^{\circ}\text{C}$ -25
Operating ambient temperature max.		$^{\circ}\text{C}$ 55
IEC/EN 61439 design verification		
10.2 Strength of materials and parts		
10.2.2 Corrosion resistance		
		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		
		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		
		Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects		
		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		
		Meets the product standard's requirements.
10.2.5 Lifting		
		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		
		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		
		Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES		
		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		
		Meets the product standard's requirements.
10.5 Protection against electric shock		
		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		
		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		
		Is the panel builder's responsibility.
10.8 Connections for external conductors		
		Is the panel builder's responsibility.
10.9 Insulation properties		
10.9.2 Power-frequency electric strength		
		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		
		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		
		Is the panel builder's responsibility.

10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Motor protection circuit-breaker (EC000074)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Motor protection circuit-breaker (ecl@ss10.0.1-27-37-04-01 [AGZ529016])			
Overload release current setting	A		0 - 0
Adjustment range undelayed short-circuit release	A		2.5 - 2.5
With thermal protection			No
Phase failure sensitive			No
Switch off technique			Magnetic
Rated operating voltage	V		690 - 690
Rated permanent current I _u	A		0.16
Rated operation power at AC-3, 230 V	kW		0
Rated operation power at AC-3, 400 V	kW		0
Type of electrical connection of main circuit			Screw connection
Type of control element			Turn button
Device construction			Built-in device fixed built-in technique
With integrated auxiliary switch			No
With integrated under voltage release			No
Number of poles			3
Rated short-circuit breaking capacity I _{cu} at 400 V, AC	kA		150
Degree of protection (IP)			IP20
Height	mm		93
Width	mm		45
Depth	mm		76