

Switch connector with fuses In-line design, pluggable NH2 400 A, 3-pole AC23A 500V , 120 (AC500V) kA manual operating without auxiliary switch without current transformer without ammeter

General technical data	
let-through I _{2t} value / at AC-22 B / at 400 V / maximum permissible	2 150 000 A²·s
let-through I _{2t} value / at AC-22 B / at 500 V / maximum permissible	2 150 000 A²·s
Voltage	
operating voltage (U _e) / rated value / maximum	690 V
Main circuit	
operational current / rated value / maximum	400 A
Mechanical Design	
height	198 mm
width	590 mm
depth	308 mm
busbar center-to-center spacing	185 mm
Environmental conditions	
installation altitude / at height above sea level / maximum	2 000 m
ambient temperature / during operation	
• minimum	-25 °C
• maximum	55 °C
Further information	
Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875	
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NJ6323-3AA00-0AA0	
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/3NJ6323-3AA00-0AA0	
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NJ6323-3AA00-0AA0	
CAX-Online-Generator http://www.siemens.com/cax	
Tender specifications http://www.siemens.com/specifications	



last modified:

3/18/2021

