

PRODUCT-DETAILS

# CT-MFS.21S

## CT-MFS.21S Time relay, multifunction 2c/o, 24-240VAC/DC



### General Information

Extended Product Type	CT-MFS.21S
Product ID	1SVR730010R0200
EAN	4016779851367
Catalog Description	CT-MFS.21S Time relay, multifunction 2c/o, 24-240VAC/DC

#### Long Description

The CT-MFS.21S is a multifunction electronic time relay from the CT-S timer range. It provides 10 timing functions with 10 time ranges from 0.05 s to 300 h. This time relay operates with a rated control supply voltage of 24 - 240 V AC / DC and has a 2 c/o (SPDT) output with contacts rated at 250 V / 4 A. Two control inputs work with volt-free (floating) triggering. The CT-MFS.21S offers the possibility of connecting a remote potentiometer for the fine adjustment of the time delay. The second of the c/o contacts can be selected as an instantaneous contact. A sealable transparent cover for protection against unauthorized changes is available as accessory. The device offers screw connection technology with double-chamber cage connection terminals.

### Ordering

EAN	4016779851367
Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

### Popular Downloads

Data Sheet, Technical Information	2CDC110004C0210_01
Instructions and Manuals	1SVC730050M1000 1SVC730050M0000

---

**Dimensions**


---

Product Net Width	22.5 mm
Product Net Height	85.6 mm
Product Net Depth / Length	103.7 mm
Product Net Weight	0.145 kg

---

**Technical**


---

Timer Relay Type	Impulse OFF Impulse ON OFF-Delay ON-Delay Star-Delta
Time Range	0.05 s ... 300 h
Rated Control Supply Voltage ( $U_s$ )	24 ... 240 V AC/DC
Rated Frequency (f)	DC 50 Hz 60 Hz
Output	2 c/o (SPDT) contacts
Terminal Type	Screw Terminals
Rated Operational Current AC-12 ( $I_{\theta}$ )	(230 V) 4 A
Rated Operational Current AC-15 ( $I_{\theta}$ )	(230 V) 3 A
Rated Operational Current DC-12 ( $I_{\theta}$ )	(24 V) 4 A
Rated Operational Current DC-13 ( $I_{\theta}$ )	(24 V) 2 A
Minimum Switching Capacity	12 V 10 mA
Rated Impulse Withstand Voltage ( $U_{imp}$ )	Input Circuit 4 kV Output Circuit 1 / Output Circuit 2 4 kV
Rated Insulation Voltage ( $U_i$ )	Input Circuit / Output Circuit 500 V Output Circuit 1 / Output Circuit 2 300 V
Degree of Protection	Housing IP50 Terminals IP20
Overvoltage Category	III
Pollution Degree	3
Short-Circuit Protective Devices	Output Circuit NC - F Type Fuses 6 A Output Circuit NO - F Type Fuses 10 A
Electrical Durability	AC-12 100000 cycle
Mechanical Durability	30000000 cycle
Connecting Capacity	Flexible with Ferrule 1x 0.5 ... 2.5 mm <sup>2</sup> Flexible with Ferrule 2x 0.5 ... 1.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1x 0.5 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2x 0.5 ... 1.5 mm <sup>2</sup> Flexible 1x 0.5 ... 2.5 mm <sup>2</sup> Flexible 2x 0.5 ... 1.5 mm <sup>2</sup> Rigid 1x 0.5 ... 4 mm <sup>2</sup> Rigid 2x 0.5 ... 2.5 mm <sup>2</sup>
Tightening Torque	0.6 ... 0.8 N·m
Wire Stripping Length	8 mm
Recommended Screw Driver	4.5 0.8 x 4 Pozidriv 1
Mounting Position	1 ... 6
Mounting on DIN Rail	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Standards	CAN/CSA C22.2 No.14 IEC/EN 63000 IEC/EN 61812-1 UL 508

---

**Technical UL/CSA**


---

Maximum Operating Voltage UL/CSA	Output Circuit 300 V AC
Contact Rating UL/CSA	B300
Connecting Capacity UL/CSA	Flexible 1x 18-14 AWG Flexible 2x 18-16 AWG Rigid 2x 20-14 AWG Rigid 1x 20-12 AWG
Tightening Torque UL/CSA	7.08 in-lb

## Environmental

Ambient Air Temperature	Operation -40 ... +60 °C Storage -40 ... +85 °C
Maximum Operating Altitude Permissible	Without Derating 2000 m
Resistance to Shock acc. to IEC 60068-2-27	30g / 3 shocks / 11 ms
RoHS Status	Following EU Directive 2011/65/EU

## Certificates and Declarations (Document Number)

CQC Certificate	CQC2007010303255979
cULus Certificate	cULus508_20110711-E140448A
Data Sheet, Technical Information	2CDC110004C0210_01
Declaration of Conformity - CCC	2020980303000207
Declaration of Conformity - CE	1SVD981008
Declaration of Conformity - UKCA	1SVD981008-10
DNV GL Certificate	DNV_GL_TAA00000XR
EAC Certificate	EAC RU C-DE.ME77.B.00568/20
Environmental Information	1SAC200095H0001
Instructions and Manuals	1SVC730050M1000 1SVC730050M0000
RMRS Certificate	RMRS_1740021250
RoHS Information	1SVD981008

## Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	97 mm
Package Level 1 Depth / Length	30 mm
Package Level 1 Height	109 mm
Package Level 1 Gross Weight	0.167 kg
Package Level 1 EAN	4016779851367

## Classifications

Object Classification Code	K
ETIM 4	EC001439 - Timer relay
ETIM 5	EC001439 - Timer relay
ETIM 6	EC001439 - Timer relay
ETIM 7	EC001439 - Timer relay
ETIM 8	EC001439 - Timer relay
eClass	V11.0 : 27371605
UNSPSC	39121519
E-Number (Finland)	2712194
E-Number (Sweden)	4033107

---

## Categories

---

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Time Relays → CT-S

