

## Control switchp11 S16A, 250 V

Part no. **Z-SW/S**  
 Catalog No. **276300**



## Design verification as per IEC/EN 61439

Technical data for design verification		
Rated operational current for specified heat dissipation	$I_n$	A 16
Heat dissipation per pole, current-dependent	$P_{vid}$	W 2
Equipment heat dissipation, current-dependent	$P_{vid}$	W 2

## Technical data ETIM 7.0

Devices for distribution board-/surface mounting (EG000062) / Main switch for distribution board (EC001545)		
Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Main switch for distribution board (ecL@ss10.0.1-27-14-23-01 [AFZ813014])		
Switching function		Control switch
Number of contacts as normally open contact		1
Number of contacts as normally closed contact		0
Number of contacts as change-over contact		0
Number of poles		1
Rated current	A	16
Rated voltage	V	250
Min. rated voltage	V	230
Rated switching capacity	kA	0.02
Short-circuit breaking capacity (Icw)	kA	0.02
Voltage type		AC
With signal lamp		No
Colour calotte		Other
Lamp type		Other
Lamp socket		Other
Max. lamp power	W	0
Width in number of modular spacings		1
Built-in depth	mm	60
Degree of protection (IP)		IP40
Imprint/indication		EV000154