

Fuse-link, high speed, 4 A, DC 1500 V, IEC 60269-6 type A, 10 x 85 mm, gPV, UL PV, UL, IEC



PV-4A10F85L

General specifications

Product name	Eaton Bussmann series photovoltaic fuses
Part no.	PV-4A10F85L
EAN	5027590506267
Product Length/Depth	85 millimetre
Product height	10 millimetre
Product width	10 millimetre
Product weight	18.6 gram
Compliances	CE Marked RoHS Compliant
Certifications	UL Listed CSA Certified IEC 60269
Product Tradename	None
Product Type	High speed photovoltaic fuse
Product Sub Type	None

Electrical data

Amperage Rating	4 A
Voltage rating	1500 Vdc
Interrupt rating	30 kAIC
Class	Class gPV

Product specifications

Application	Photovoltaic systems, inverters ,Photovoltaic strings
Fuse type	PV-A10F85L
Fuse indicator	Non Indicating
Fuse size	10 x 85 mm

Compatible fuse holders

Suitable for	CHPV15L85 Fuse holder
--------------	-----------------------

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss13-27-14-20-02 [AFZ797018])		
Model		Fiberglass fuse
Size		Other
Voltage type		DC
Rated current	A	4
Rated voltage	V	1500
Utilization category		gPV (photovoltaic protection)
Rated operating frequency	Hz	
Type of fuse status indicator		Other
Release characteristic		Other
Breaking capacity	kA	30
Power loss at rated current	W	2.8