

Pushbutton, white, momentary

**Part no.** Q25D-WS  
**Catalog No.** 086808  
**Alternate Catalog No.** Q25D-WS

### Delivery program

|                            |   |    |                      |
|----------------------------|---|----|----------------------|
| Product range              |   |    | RMQ16                |
| Basic function             |   |    | Pushbutton actuators |
| Mounting hole diameter     | ∅ | mm | 16                   |
| Single unit/Complete unit  |   |    | Single unit          |
| Design                     |   |    | Flat                 |
|                            |   |    | momentary            |
| <b>Button plate</b>        |   |    |                      |
| button plate               |   |    | White                |
|                            |   |    | Blank                |
| Degree of Protection       |   |    | IP65                 |
| Front ring                 |   |    | without bezel        |
| Connection to SmartWire-DT |   |    | no                   |

### Technical data

#### General

|                                    |              |                   |  |
|------------------------------------|--------------|-------------------|--|
| Standards                          |              |                   | IEC/EN 60947, VDE 0660   |
| Lifespan, mechanical               | Operations   | x 10 <sup>6</sup> | > 3  |
| Operating frequency                | Operations/h |                   | ≤ 3600   |
| Actuating force                    |              | n                 | ≤ 4  |
| Degree of protection, IEC/EN 60529 |              |                   | IP65   |
| Climatic proofing                  |              |                   | Damp heat, constant, to IEC 60068-2-78<br>Damp heat, cyclic, to IEC 60068-2-30 |
| Ambient temperature                |              |                   |  |
| Open                               |              | °C                | -25 - +60  |
| Enclosed                           |              | °C                | - 25 - 40  |
| Mounting position                  |              |                   | As required  |
| Mechanical shock resistance        |              | g                 | > 40<br>according to IEC 60068-2-27<br>Shock duration 11 ms<br>Sinusoidal      |

### Design verification as per IEC/EN 61439

|  |                   |    |  |
|--|-------------------|----|--|
| Technical data for design verification   |                   |    |  |
| Rated operational current for specified heat dissipation   | I <sub>n</sub>    | A  | 0  |
| Heat dissipation per pole, current-dependent   | P <sub>vid</sub>  | W  | 0  |
| Equipment heat dissipation, current-dependent  | P <sub>vid</sub>  | W  | 0  |
| Static heat dissipation, non-current-dependent   | P <sub>vs</sub>   | W  | 0  |
| Heat dissipation capacity  | P <sub>diss</sub> | W  | 0  |
| Operating ambient temperature min.   |                   | °C | -25  |
| Operating ambient temperature max.   |                   | °C | 60   |
| IEC/EN 61439 design verification   |                   |    |  |
| 10.2 Strength of materials and parts   |                   |    |  |
| 10.2.2 Corrosion resistance  |                   |    |  |
|  |                   |    | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures   |                   |    |  |
|  |                   |    | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat   |                   |    |  |
|  |                   |    | Meets the product standard's requirements. |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects |                   |    |  |
|  |                   |    | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation   |                   |    |  |
|  |                   |    | Please enquire                             |

|  |  |  |
|--|--|--|
| 10.2.5 Lifting   |  | Does not apply, since the entire switchgear needs to be evaluated.                                       |
| 10.2.6 Mechanical impact                                 |  | Does not apply, since the entire switchgear needs to be evaluated.                                       |
| 10.2.7 Inscriptions                                      |  | Meets the product standard's requirements.   |
| 10.3 Degree of protection of ASSEMBLIES                  |  | Does not apply, since the entire switchgear needs to be evaluated.                                       |
| 10.4 Clearances and creepage distances                   |  | Meets the product standard's requirements.   |
| 10.5 Protection against electric shock                   |  | Does not apply, since the entire switchgear needs to be evaluated.                                       |
| 10.6 Incorporation of switching devices and components   |  | Does not apply, since the entire switchgear needs to be evaluated.                                       |
| 10.7 Internal electrical circuits and connections        |  | Is the panel builder's responsibility.   |
| 10.8 Connections for external conductors                 |  | Is the panel builder's responsibility.   |
| 10.9 Insulation properties                               |  |  |
| 10.9.2 Power-frequency electric strength                 |  | Is the panel builder's responsibility.   |
| 10.9.3 Impulse withstand voltage                         |  | Is the panel builder's responsibility.   |
| 10.9.4 Testing of enclosures made of insulating material |  | Is the panel builder's responsibility.   |
| 10.10 Temperature rise                                   |  | Not applicable.  |
| 10.11 Short-circuit rating                               |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.           |
| 10.12 Electromagnetic compatibility                      |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.           |
| 10.13 Mechanical function                                |  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

## Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Front element for push button (EC000221)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for push-button actuators (ecl@ss10.0.1-27-37-12-10 [AKF028014])

|   |    |         |
|---|----|---------|
| Colour button                           |    | White   |
| Number of command positions             |    | 1       |
| Construction type lens                  |    | Square  |
| Hole diameter                           | mm | 16      |
| Width opening                           | mm | 0       |
| Height opening                          | mm | 0       |
| Type of button                          |    | Flat    |
| Suitable for illumination               |    | No      |
| With protective cover                   |    | No      |
| Labelled                                |    | No      |
| Switching function latching             |    | No      |
| Spring-return                           |    | Yes     |
| With front ring                         |    | Yes     |
| Material front ring                     |    | Plastic |
| Colour front ring                       |    | Black   |
| Degree of protection (IP), front side   |    | IP65    |
| Degree of protection (NEMA), front side |    | 1       |