

Complete surface-mounted flat distribution board, white, 24 SU per row, 5 rows, type P



Part no. **BF-0-5/120-P**
 Catalog No. **285347**

Delivery program

Basic function		Basic device
Product function		Installation distribution boards
Product range		BF flat DBO
Design		Surface mounted
Installation site		Indoor
Type of installation		Surface mounting
Door/Flap		White
Degree of Protection		IP30
Colour		White
Module rack		Rail-frame
Shroud for protection against accidental contact		Metal
Rows	Count	5
Module units per row		24
Description		IP30 Protection Class I Steel sheet enclosure white (RAL 9016)
Cable entries		Cable entries on top and bottom
PE and N terminals design		Screw terminals
PE and N terminals	Number x cross- sectional area	mm ² PE: 2 x 25 + 58 x 16 N: 2 x 25 + 58 x 16
Equipment supplied		Enclosure Door with three-point turn-lock DIN rail mounting frame Cable gland plate inserts (top) Front plates Neutral-/protective conductor terminal

Technical data

General		
Standards	IEC/EN 61439-1, IEC/EN 61439-3, IEC/EN 62208	
RoHS (in accordance with Directive 2002/95/EC of the European Parliament and Council)	conform	
Ambient temperature	°C -5 - +40	
Degree of Protection	IP30	
Protection class	I (earthed)	
Rated operational voltage	Ue	V AC 415
Rated frequency	f	Hz 50/60

Material characteristics

Material		Sheet steel, powder-coated
Colour		white (RAL 9016)

Material properties

Mechanical		
Impact resistance		IK07

Design verification as per IEC/EN 61439

Technical data for design verification			
Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890			
Individual enclosure for wall mounting	P _V	W	59
Starting enclosure for wall mounting	P _V	W	56

Middle enclosure for wall mounting	P _V	W	53
Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees in top of the enclosure, calculated as per IEC 60890			
Individual enclosure for wall mounting	P _V	W	118
Starting enclosure for wall mounting	P _V	W	112
Middle enclosure for wall mounting	P _V	W	107
IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Not relevant to indoor installations.
10.2.5 Lifting			Does not apply to enclosures without lifting aids.
10.2.6 Mechanical impact			IK07
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES			IP30
10.4 Clearances and creepage distances			Is the panel builder's responsibility.
10.5 Protection against electric shock			< 0.1 Ω; meets the product standard's requirements.
10.6 Incorporation of switching devices and components			Is the panel builder's responsibility.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9 Insulation properties			
10.9.2 Power-frequency electric strength			U _i = 415 V AC
10.9.3 Impulse withstand voltage			Does not apply to basic enclosures as defined in EN 62208.
10.9.4 Testing of enclosures made of insulating material			Does not apply to metal enclosures.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility.
10.13 Mechanical function			Meets the product standard's requirements.

Technical data ETIM 8.0

Distribution boards (EG000023) / Small distribution board (EC000214)

Electric engineering, automation, process control engineering / Electrical installation, device / Electrical distribution system (incl. small distribution board) / Small distribution board (ecl@ss10.0.1-27-14-24-09 [ACN387011])

Mounting method		Surface mounted (plaster)
Number of rows		5
Width in number of modular spacings		24
Type of cover		Door
Cover model		Closed
Transparent cover/door		No
Material housing		Steel
Height	mm	145
Width	mm	570
Depth	mm	915
Built-in depth	mm	915
Built-in height	mm	145
Built-in width	mm	570
Internal depth	mm	131
Earthing terminal block		Yes
Neutral terminal block		Yes
DIN-rail		Yes
With mounting plate		No
Extension possible		No

EMC-version		Yes
Colour		White
RAL-number		9016
Degree of protection (IP)		IP30
With lock		No
Type of closure		Other
Signal passing door		No