

---

**PRODUCT-DETAILS**

## **BW325TPN**

### **BW325TPN Enclosed Switch Disconnector**



---

#### **General Information**

Extended Product Type	BW325TPN
Product ID	2CMA142403R1000
EAN	7392696424035
Catalog Description	BW325TPN Enclosed Switch Disconnector
Long Description	<p>Encl. Switch Disconnector, 3-p. 415V AC23 16A, 7.5kW. Plastic enclosure. IP65. Grey Side-operated handle. Interlocked cover. The enclosure of the ABB's side controlled enclosed switches is made of rigid polycarbonate. The enclosure is UV protected, and protected against low pressure water jets (IP65), and hence built for outdoor and indoor use. The enclosure is available in different colors, grey, yellow and white. The cable entries are threaded and have knock out holes for 2 parallel cables, both from top and bottom. Membrane grommets are included (IP54). The handle is padlockable and made for one padlock. The cover is interlocked. The switch is made for 5 wire system, and have a fixed neutral terminal and PE terminal. The terminals are easily accessible for easy installation.</p>

---

#### **Ordering**

Minimum Order Quantity	1 piece
Customs Tariff Number	85363030
Country of Origin	Bulgaria (BG)

---

#### **Popular Downloads**

Data Sheet, Technical Information	1SCC340015C0201
Instructions and	9AKK108467A6812

## Manuals

## Mechanical Drawings

BAS1131160DM25.stp

**Dimensions**

Product Net Width	111 mm
Product Net Height	130 mm
Product Net Depth / Length	60 mm
Product Net Weight	0.31 kg

**Technical**

Rated Operational Current AC-22A ( $I_e$ )	(380 ... 415 V) 25 A (690 V) 16 A
Rated Operational Current AC-23A ( $I_e$ )	(380 ... 415 V) 16 A (500 V) 16 A (690 V) 10 A
Rated Operational Power AC-23A ( $P_e$ )	(380 ... 415 V) 7.5 kW (500 V) 7.5 kW (690 V) 7.5 kW
Conventional Free-air Thermal Current ( $I_{th}$ )	32 A
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 25 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	8 kV
Rated Insulation Voltage ( $U_i$ )	acc. to IEC/EN 60664-1 690 V
Rated Operational Voltage	Main Circuit 690 V
Handle Color	Grey
Handle Type	Side-operated handle
Standards	IEC 60947-1, -3
Number of Poles	3
Neutral Type	Fixed neutral
Connecting Capacity Main Circuit	Screw Clamp 0.75 ... 10 mm <sup>2</sup> Screw Clamp / PE Terminal 1pc, 0.75 ... 10 mm <sup>2</sup>
Cable Cross-Section	0.75 ... 10 mm <sup>2</sup>
Cable Entry Position	Up/Down
Cable Outlets Per Side	2xM25 / 2xM25
Degree of Protection	acc. to IEC 60529 IP65
Impact Resistance Rating	Housing IK08
Enclosure Material	Plastic
Maximum Mounted Auxiliary Contacts	1 NO, 0 NC
Mounted Auxiliary Contacts	0 NO, 0 NC
Number of Auxiliary Contacts NC	0
Number of Auxiliary Contacts NO	0
Tightening Torque	Main Circuit 1.2 N·m
Rated Current ( $I_n$ )	25 A

**Technical UL/CSA**

Tightening Torque	Main Circuit 1.2 N·m
-------------------	----------------------

**Environmental**

RoHS Status	Following EU Directive 2011/65/EU
RoHS Date	2009-01

**Certificates and Declarations (Document Number)**

Declaration of Conformity - CE	1SCC340062D2702
Instructions and Manuals	9AKK108467A6812
REACH Declaration	1SCC340076D0201
RoHS Information	1SCC340075D0201

**Container Information**

Package Level 1 Units	box 1 piece
Package Level 1 Width	112 mm
Package Level 1 Depth / Length	131 mm
Package Level 1 Height	62 mm
Package Level 1 Gross Weight	0.31 kg
Package Level 1 EAN	7392696424035

**Classifications**

Object Classification Code	Q 2CMT005069
ETIM 4	EC000216 - Switch disconnector
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector
ETIM 8	EC000216 - Switch disconnector
UNSPSC	39120000
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

**Categories**

Low Voltage Products and Systems → Enclosed Switches → Enclosed Switch-Disconnectors → Enclosed Switch-Disconnectors

