



Switch disconnecter 63 A, Size 1, 3-pole Lateral operating mechanism left Basic unit without handle Box terminal

| Model                                                                                         |                           |
|-----------------------------------------------------------------------------------------------|---------------------------|
| product brand name                                                                            | SETRON                    |
| product designation                                                                           | 3KD switch disconnecter   |
| design of the product                                                                         | Switch                    |
| display version for switch position indicator door-coupling rotary operating mechanism        | ON-OFF                    |
| design of the actuating element                                                               | Without handle            |
| type of the driving mechanism                                                                 | Side operating mechanism  |
| type of the driving mechanism motor drive                                                     | No                        |
| General technical data                                                                        |                           |
| number of poles                                                                               | 3                         |
| type of device                                                                                | fixed mounting            |
| size of switch disconnecter                                                                   | 1                         |
| mechanical service life (operating cycles) typical                                            | 15 000                    |
| electrical endurance (operating cycles)                                                       |                           |
| • at AC-23 A at 690 V                                                                         | 6 000                     |
| • at DC-23 A at 440 V                                                                         | 1 500                     |
| I <sup>2</sup> t value                                                                        |                           |
| • with closed switch at 1000 V for combination switch +gG/aM SITOR fuse maximum               | 2 331 A <sup>2</sup> ·s   |
| • of the gG/aM SITOR fuse at 1000 V maximum permissible                                       | 6 000 A <sup>2</sup> ·s   |
| • of the molded case circuit breaker at 415 V maximum permissible                             | 480 000 A <sup>2</sup> ·s |
| position of the switch operating mechanism                                                    | at the left end           |
| overvoltage in percent relative to the operating voltage at AC at 400, 500, 690 V at 50/60 Hz | 10 %                      |
| overvoltage category                                                                          | III                       |
| degree of pollution                                                                           | 3                         |
| Voltage                                                                                       |                           |
| operating voltage with current paths in series                                                |                           |
| • with degree of pollution 2 at DC rated value                                                | 440 V / 3                 |
| • with degree of pollution 3 at DC rated value                                                | 440 V / 3                 |
| insulation voltage                                                                            |                           |
| • rated value                                                                                 | 1 000 V                   |
| surge voltage resistance rated value                                                          | 8 kV                      |
| operational current at AC-22 A at 1000 V maximum                                              | 63 A                      |
| Protection class                                                                              |                           |
| protection class IP                                                                           | IP20                      |
| protection class IP                                                                           |                           |
| • with closed switch with cover or cable lug cover                                            | IP20                      |
| • on the front                                                                                | IP20                      |

|                                                                                                  |                                               |
|--------------------------------------------------------------------------------------------------|-----------------------------------------------|
| <b>Dissipation</b>                                                                               |                                               |
| power loss [W]                                                                                   |                                               |
| • with conventional rated thermal current per pole                                               | 1 W                                           |
| • with conventional rated thermal current per device                                             | 3 W                                           |
| • for rated value of the current at AC in hot operating state per pole                           | 1 W                                           |
| <b>Main circuit</b>                                                                              |                                               |
| operating power                                                                                  |                                               |
| • at AC-23 A at 500 V rated value                                                                | 37 kW                                         |
| operational current rated value                                                                  | 63 A                                          |
| <b>Auxiliary circuit</b>                                                                         |                                               |
| number of connected NC contacts for auxiliary contacts                                           | 0                                             |
| number of connected NO contacts for auxiliary contacts                                           | 0                                             |
| number of connected CO contacts for auxiliary contacts                                           | 0                                             |
| number of CO contacts for auxiliary contacts                                                     | 3                                             |
| number of NC contacts for auxiliary contacts                                                     | 0                                             |
| number of NO contacts for auxiliary contacts                                                     | 0                                             |
| <b>Suitability</b>                                                                               |                                               |
| suitability for use                                                                              |                                               |
| • main switch                                                                                    | Yes                                           |
| • switch disconnecter                                                                            | Yes                                           |
| • EMERGENCY OFF switch                                                                           | Yes                                           |
| • safety switch                                                                                  | Yes                                           |
| • maintenance/repair switch                                                                      | Yes                                           |
| <b>Product details</b>                                                                           |                                               |
| product component                                                                                |                                               |
| • trip indicator                                                                                 | No                                            |
| • voltage trigger                                                                                | No                                            |
| • undervoltage release                                                                           | No                                            |
| • undervoltage release with leading contact                                                      | No                                            |
| product extension auxiliary switch                                                               | Yes                                           |
| <b>product extension optional</b>                                                                |                                               |
| • motor drive                                                                                    | No                                            |
| • voltage trigger                                                                                | No                                            |
| <b>Short circuit</b>                                                                             |                                               |
| short-time withstand current (I <sub>cw</sub> ) at 1000 V AC/440 V DC limited to 1 s rated value | 3 kA                                          |
| short-circuit current making capacity (I <sub>cm</sub> ) for switch disconnecter                 |                                               |
| • at 1000 V AC without fuse link rated value minimum                                             | 7 kA                                          |
| • at DC 440 V without fuse link rated value minimum                                              | 7 kA                                          |
| • without fuse link rated value minimum                                                          | 7 kA                                          |
| conditional short-circuit current with line-side fuse protection                                 |                                               |
| • at 415 V by molded case circuit breaker rated value                                            | 36 kA                                         |
| • at 500 V by gG fuse rated value                                                                | 100 kA                                        |
| • at 690 V by gG fuse rated value                                                                | 100 kA                                        |
| <b>Connections</b>                                                                               |                                               |
| type of connectable conductor cross-sections with flexible busbar                                | 2x (0,8x9 mm <sup>2</sup> )                   |
| type of connectable conductor cross-sections                                                     |                                               |
| • for copper busbar                                                                              | '1 x (2 x 9 mm <sup>2</sup> )                 |
| type of connectable conductor cross-sections for copper conductor                                |                                               |
| • solid                                                                                          | 1x (1 ... 16 mm <sup>2</sup> )                |
| • finely stranded with core end processing                                                       | 1x (1 ... 35 mm <sup>2</sup> )                |
| • stranded                                                                                       | 1x (6 ... 35 mm <sup>2</sup> )                |
| type of electrical connection for main current circuit                                           | box terminal                                  |
| <b>Mechanical Design</b>                                                                         |                                               |
| height                                                                                           | 119 mm                                        |
| width                                                                                            | 103.3 mm                                      |
| depth                                                                                            | 70 mm                                         |
| fastening method                                                                                 | Screw fixing and standard rail mounting 35 mm |

|                                          |       |
|------------------------------------------|-------|
| fastening method                         |       |
| • 4-hole front mounting                  | No    |
| • front mounting with central attachment | No    |
| • rail mounting                          | Yes   |
| mounting position                        | any   |
| net weight                               | 880 g |

#### Environmental conditions

|                                      |        |
|--------------------------------------|--------|
| ambient temperature during operation |        |
| • minimum                            | -25 °C |
| • maximum                            | 70 °C  |
| ambient temperature during storage   |        |
| • minimum                            | -50 °C |
| • maximum                            | 80 °C  |

#### Certificates

|                                         |   |
|-----------------------------------------|---|
| reference code according to IEC 81346-2 | Q |
|-----------------------------------------|---|

#### Approvals Certificates

##### General Product Approval



[Confirmation](#)



[Miscellaneous](#)

| General Product Approval | Test Certificates | Marine / Shipping | other |
|--------------------------|-------------------|-------------------|-------|
|--------------------------|-------------------|-------------------|-------|



[Type Test Certificates/Test Report](#)



[Miscellaneous](#)




[Confirmation](#)

#### Environment

[Environmental Conformations](#)

#### Further information

Information on the packaging  
<https://support.industry.siemens.com/cs/ww/en/view/109813875>  
 Information- and Downloadcenter (Catalogs, Brochures,...)  
<http://www.siemens.com/lowvoltage/catalogs>  
 Industry Mall (Online ordering system)  
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3KD2634-2ME10-0>  
 Service&Support (Manuals, Certificates, Characteristics, FAQs,...)  
<https://support.industry.siemens.com/cs/ww/en/ps/3KD2634-2ME10-0>  
 Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)  
[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3KD2634-2ME10-0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3KD2634-2ME10-0)  
 CAx-Online-Generator  
<http://www.siemens.com/cax>  
 Tender specifications  
<http://www.siemens.com/specifications>





-Q

~~1~~

3




5




2

4

6



# -CR



---

last modified:

2/1/2024 

