

Socket outlet 1-position; with EURO2 adapter; with plug-in units; without input wiring



Part no. **S1-KLV**
 Catalog No. **178970**

Delivery program

| | | |
|----------------|--|-----------------------------------|
| Basic function | | Accessory consideration |
| Accessories | | KLV |
| Product range | | KLV multimedia KLV Accessories |

Technical data ETIM 8.0

| | |
|--|-----------------------------|
| Domestic switching devices (EG000013) / Socket outlet (EC000125) | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Installation switch set / Plug socket (ecl@ss10.0.1-27-14-40-42 [AKE352014]) | |
| Model | Protective contact (SCHUKO) |
| Protective contact | Yes |
| Protective earth pin round | No |
| Number of active pins (round) | 2 |
| Number of active pins (flat) | 0 |
| With signal lamp | No |
| With built-in USB power supply | No |
| Type of USB power supply | Other |
| Number of units | 1 |
| Number of modules (module system) | 1 |
| Number of socket outlets switchable | 0 |
| Number of phases | 2 |
| Imprint/indication | None |
| Connection type | Push-in clamp |
| With hinged lid | No |
| With enhanced contact protection | No |
| Label space/information surface | No |
| Colour | White |
| RAL-number (similar) | 9010 |
| Metallic colour | No |
| Transparent | No |
| Lockable | No |
| Eject-mechanism | No |
| Insulated mounting | Yes |
| With function lighting | No |
| With orientation lighting | No |
| Over voltage protection | No |
| Fault current protection | No |
| With miniature fuse | No |
| Special power supply | Other |
| Mounting method | Other |
| Type of fastening | Mounting with screw |
| Material | Plastic |
| Material quality | Thermoplastic |
| Halogen free | Yes |
| Surface protection | Other |
| Surface finishing | Glossy |
| Anti-bacterial treatment | No |
| With on/off switch | No |

| | | |
|---|----|---------|
| With loop through function | | Yes |
| Rotated central insert | | No |
| Nominal current | A | 16 |
| Nominal voltage | V | 230 |
| Frequency | Hz | 50 - 50 |
| Rated fault current | mA | 1000 |
| Suitable for degree of protection (IP) | | IP00 |
| Impact strength | | Other |
| Width of device | mm | 61 |
| Height of device | mm | 61 |
| Depth of device | mm | 47 |
| Compatible with Apple HomeKit | | No |
| Compatible with Google Assistant | | No |
| Min. depth of built-in installation box | mm | 36 |
| Compatible with Amazon Alexa | | No |
| IFTTT support available | | No |
| For heavy conditions (according to VDE) | | No |