
PRODUCT-DETAILS

SD201/40

SD201/40 Switch Disconnectors



General Information

| | |
|-----------------------|--------------------------------------|
| Extended Product Type | SD201/40 |
| Product ID | 2CDD281101R0040 |
| EAN | 4016779904094 |
| Catalog Description | SD201/40 Switch Disconnectors |
| Long Description | SD201/40 Switch Disconnector 1P, 40A |

Technical

| | |
|--|--|
| Standards | IEC/EN 60947-3 |
| Rated Voltage (U_r) | 253 V 12 V Minimum |
| Rated Operational Voltage | 253 V AC 60 V DC |
| Operational Voltage | Maximum 266 V AC Maximum 63 V DC Minimum 12 V AC |
| Rated Impulse Withstand Voltage (U_{imp}) | 4 kV at 2000 m 5 kV at Sea Level 6.2 kV |
| Input Voltage Type | AC/DC |
| Rated Current (I_n) | 40 A |
| Rated Conditional Short-Circuit Current (I_{nc}) | 25 kA |
| Rated Service Short- | 25 kA |

| | |
|--|--|
| Circuit Breaking Capacity (I_{cs}) | |
| Rated Frequency (f) | 50 / 60 Hz DC |
| Power Loss | at Rated Operating Conditions per Pole 2.27 W |
| Contact Position Indication | ON / OFF |
| Electrical Endurance | 10000 AC cycle |
| Mechanical Endurance | 20000 cycle |
| Number of Poles | 1 |
| Number of Contacts CO | 0 |
| Number of Contacts NC | 0 |
| Number of Contacts NO | 1 |
| Overvoltage Category | III |
| Tightening Torque | 2.8 N·m |
| Utilization Category | Switching of motor loads or other highly inductive loads - frequent actuation (AC-23A) Switching of resistive loads, including moderate overloads - frequent actuation (DC-21A) |
| Actuator Type | Toggle |
| Screw Terminal Type | Failsafe Bi-directional Cylinder-lift Terminal |
| Switch Type | Off |
| Actuator Marking | I / O |
| Actuator Material | Insulation Group II, Red, Sealable |
| Housing Material | Insulation Group I, RAL 7035 |
| Mounting Position | any |
| Recommended Screw Driver | Pozidriv 2 |
| Accessories Available | Yes |
| Cover Color | Grey |
| Connecting Capacity | Busbar 10 / 10 mm ² Flexible 0.75 ... 16 mm ² Rigid 0.75 ... 25 mm ² Stranded 0.75 ... 25 mm ² |
| Terminal Type | Screw Terminals |

Environmental

| | |
|--|---|
| Ambient Air Temperature | Operation -25 ... +55 °C Storage -40 ... +70 °C |
| Degree of Protection | IP20 Enclosure with Cover IP40 |
| Pollution Degree | 3 |
| Environmental Conditions | 28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 % |
| Resistance to Vibrations acc. to IEC 60068-2-6 | 5g, 20 cycles at 5 ... 150 ... 5 Hz with load 0.8 In |
| Resistance to Shock acc. to IEC 60068-2-27 | 25g / 2 shocks / 13 ms |
| RoHS Status | Following EU Directive 2011/65/EU |
| Environmental Information | 2CDK400618D0201 |
| REACH Declaration | 9AKK107492A1906 |

Dimensions

| | |
|-------------------------------------|---|
| Width in Number of Modular Spacings | 1 |
|-------------------------------------|---|

| | |
|----------------------------------|----------|
| Product Net Width | 17.5 mm |
| Product Net Height | 88 mm |
| Product Net Depth / Length | 69 mm |
| Product Net Weight | 0.085 kg |
| Built-In Depth (t ₂) | 69 mm |

Container Information

| | |
|--------------------------------|-----------------|
| Package Level 1 Units | carton 10 piece |
| Package Level 1 Width | 92 mm |
| Package Level 1 Height | 80 mm |
| Package Level 1 Depth / Length | 183 mm |
| Package Level 1 Gross Weight | 0.9 kg |
| Package Level 1 EAN | 4016779904575 |
| Package Level 2 Units | 120 piece |
| Package Level 2 Width | 275 mm |
| Package Level 2 Height | 210 mm |
| Package Level 2 Depth / Length | 395 mm |
| Package Level 2 Gross Weight | 11.2 kg |
| Package Level 2 EAN | 4016779905053 |

Ordering

| | |
|------------------------|---------------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85369095 |
| E-Number (Finland) | 3601627 |
| Country of Origin | Bulgaria (BG) |

Certificates and Declarations (Document Number)

| | |
|--------------------------------|-----------------|
| Certification Agency | IEC EN |
| Declaration of Conformity - CE | 2CDK440034D2703 |
| Environmental Information | 2CDK400618D0201 |
| Instructions and Manuals | 2CDC441015D0201 |
| REACH Declaration | 9AKK107492A1906 |
| RoHS Information | 2CDK440036D0202 |

Popular Downloads

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 2CDC441015D0201 |
| Instructions and Manuals | 2CDC441015D0201 |

Classifications

| | |
|--------|---|
| ETIM 7 | EC001545 - Main switch for distribution board |
|--------|---|

| | |
|----------------------------|---|
| ETIM 8 | EC001545 - Main switch for distribution board |
| EPLAN Catalog Tree | Electrical engineering / Sensor, switch, and pushbutton / Switch , pushbutton |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |
| CN8 | 8536 90 95 |
| eClass | V11.0 : 27142301 |
| Object Classification Code | Q |

Accessories

| Identifier | Description | Type | Quantity | Unit Of Measure |
|-----------------|--------------------------------------|---------------|----------|-----------------|
| 2CDS200922R0001 | S2C-S/H6R Signal / Auxiliary Contact | S2C-S/H6R | 1 | piece |
| 2CDS200912R0001 | S2C-H6R Auxiliary Contact | S2C-H6R | 1 | piece |
| 2CDS200936R0001 | S2C-H11L Auxiliary Contact | S2C-H11L | 1 | piece |
| 2CDS200936R0002 | S2C-H20L Auxiliary Contact | S2C-H20L | 1 | piece |
| 2CDS200936R0003 | S2C-H02L Auxiliary Contact | S2C-H02L | 1 | piece |
| 2CDS200946R0001 | S2C-H6-11R Auxiliary Contact | S2C-H6-11R | 1 | piece |
| 2CDS200946R0002 | S2C-H6-20R Auxiliary Contact | S2C-H6-20R | 1 | piece |
| 2CDS200946R0003 | S2C-H6-02R Auxiliary Contact | S2C-H6-02R | 1 | piece |
| 2CDS200909R0001 | S2C-A1 Shunt Trip | S2C-A1 | 1 | piece |
| 2CDS200909R0002 | S2C-A2 Shunt Trip | S2C-A2 | 1 | piece |
| 2CSS200911R0001 | S2C-UA 12 DC Undervoltage release | S2C-UA 12 DC | 1 | piece |
| 2CSS200911R0002 | S2C-UA 24 AC Undervoltage release | S2C-UA 24 AC | 1 | piece |
| 2CSS200911R0003 | S2C-UA 48 AC Undervoltage release | S2C-UA 48 AC | 1 | piece |
| 2CSS200911R0004 | S2C-UA 110 AC Undervoltage release | S2C-UA 110 AC | 1 | piece |
| 2CSS200911R0005 | S2C-UA 230 AC Undervoltage release | S2C-UA 230 AC | 1 | piece |
| 2CSS200911R0006 | S2C-UA 400 AC Undervoltage release | S2C-UA 400 AC | 1 | piece |
| 2CSS200911R0007 | S2C-UA 24 DC Undervoltage release | S2C-UA 24 DC | 1 | piece |
| 2CSS200911R0008 | S2C-UA 48 DC Undervoltage release | S2C-UA 48 DC | 1 | piece |
| 2CSS200911R0009 | S2C-UA 110 DC Undervoltage release | S2C-UA 110 DC | 1 | piece |
| 2CSS200911R0010 | S2C-UA 230 DC Undervoltage release | S2C-UA 230 DC | 1 | piece |
| 2CSS201997R0013 | S2C-CM1 Motor operating device | S2C-CM1 | 1 | piece |
| 2CSS203997R0013 | S2C-CM2/3 Motor operating device | S2C-CM2/3 | 1 | piece |
| 2CSS204997R0013 | S2C-CM4 Motor operating device | S2C-CM4 | 1 | piece |
| GHS2001901R0003 | S2C-DH Mechanical Accessories | S2C-DH | 1 | piece |
| 2CSS200998R0001 | S2C-BP Mechanical tripping device | S2C-BP | 1 | piece |
| 2CSS200999R0001 | S2C-EST Plug-in base | S2C-EST | 1 | piece |
| 2CDS200918R0001 | S2C-NT Hand Operated Neutral | S2C-NT | 1 | piece |
| 2CCA880100R0001 | CMS-100PS Sensor | CMS-100PS | 1 | piece |
| 2CCA880101R0001 | CMS-101PS Sensor | CMS-101PS | 1 | piece |
| 2CCA880102R0001 | CMS-102PS Sensor | CMS-102PS | 1 | piece |

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Command and Signalling Devices → Switch Disconnectors

