



self-tapping countersunk head screw DIN 7500-QE, M6 x 12, steel, zinc-plated, TX 30, 1 pack = 100 units

<b>product feature</b>	
<ul style="list-style-type: none"> <li>• hardened</li> <li>• self-drilling</li> </ul>	No No
length	12 mm
Thread-dimension (metric)	6 mm
Thread diameter	6 mm
thread pitch	1 mm
material	steel

**Approvals Certificates**

**General Product Approval**



EG-Konf.

[Miscellaneous](#)

[Confirmation](#)



VDE

[Miscellaneous](#)

General Product Ap- proval	other	Environment
-------------------------------	-------	-------------



[Miscellaneous](#)

[Confirmation](#)

[Environmental Con-  
firmations](#)

[Environmental Con-  
firmations](#)

**Further information**

- Information on the packaging  
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
- Information- and Downloadcenter (Catalogs, Brochures,...)  
<http://www.siemens.com/lowvoltage/catalogs>
- Industry Mall (Online ordering system)  
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8PQ9500-1BA07>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)  
<https://support.industry.siemens.com/cs/ww/en/ps/8PQ9500-1BA07>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)  
[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=8PQ9500-1BA07](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8PQ9500-1BA07)
- CAX-Online-Generator  
<http://www.siemens.com/cax>
- Tender specifications  
<http://www.siemens.com/specifications>



---

last modified:

12/20/2023 