

Data sheet for SIMOTICS S-1FL6



Figure similar

MLFB-Ordering data

1FL6042-2AF21-1AH1

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

Engineering data		Mechanical data			
Rated speed	3000 rpm	Motor type	Low Inertia		
Rated torque (100 K)	2.39 Nm	Motor type	Permanent-magnet synchronous motor		
Rated current	4.7 A	Shaft height	40		
Rated power	0.75 kW / 1.02 hp	Encoder system	Incremental encoder TTL, 2500 S/R (13 bit)		
Max. speed	5000 rpm	Cooling	Natural cooling		
Maximum torque	7.20 Nm	Shaft end	Plain shaft		
Max. current	14.2 A	Radial runout tolerance	Class N		
Static torque	2.39 Nm	Vibration severity grade	Grade A		
Moment of inertia	1.060 kgcm ²	Degree of protection	IP65		
Physical constants		Design acc. to Code I	IM B5 (IM V1, IM V3)		
		Torque constant	0.51 Nm/A	Connection type	Cable outlet
		Thermal class	B (130 °C)	Holding brake	
Net weight	3.70 kg	Holding torque M_{4Br}	3.18 Nm		
Ambient conditions		Rated voltage	24 V DC 10 %		
		Ambient temperature	0 ... 40 °C		
Relative humidity		Opening time	105 ms		
		Max. operation	90 % RH maximum (no condensation at 30 °C)		
Standards		Closing time	15 ms		
		Compliance with standards	CE, EAC		
		Rated current	0.35 A		