



SIMATIC ET 200SP, Digital output module, DQ 16x 24V DC/0,5A  
 Standard, Source output (PNP,P-switching) Packing unit: 1 piece, fits to  
 BU-type A0, Colour Code CC00, substitute value output, module  
 diagnostics for: short-circuit to L+ and ground, wire break, supply voltage

### General information

Product type designation	DQ 16x24VDC/0.5A ST
HW functional status	From FS03
Firmware version	V0.0
• FW update possible	No
usable BaseUnits	BU type A0
Color code for module-specific color identification plate	CC00
Product function	
• I&M data	Yes; I&M0 to I&M3
• Isochronous mode	No
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	V14
• STEP 7 configurable/integrated from version	V5.5 SP3
• PCS 7 configurable/integrated from version	V8.1 SP1
• PROFIBUS from GSD version/GSD revision	One GSD file each, Revision 3 and 5 and higher
• PROFINET from GSD version/GSD revision	GSDML V2.3

### Operating mode

• DQ	Yes
• DQ with energy-saving function	No
• PWM	No
• Oversampling	No
• MSO	No

### Supply voltage

Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes

### Input current

Current consumption, max.	60 mA; without load
---------------------------	---------------------

### Output voltage / header

Rated value (DC)	24 V
------------------	------

### Power loss

Power loss, typ.	1 W
------------------	-----

### Address area

Address space per module	
• Address space per module, max.	2 byte; + 2 bytes for QI information

### Hardware configuration

Automatic encoding	Yes
• Mechanical coding element	Yes

• Type of mechanical coding element		Type A
Selection of BaseUnit for connection variants		
• 1-wire connection		BU type A0
• 2-wire connection		BU type A0 + Potential distributor module
• 3-wire connection		BU type A0 + Potential distributor module
• 4-wire connection		BU type A0 + Potential distributor module
<b>Digital outputs</b>		
Type of digital output		Source output (PNP, current-sourcing)
Number of digital outputs		16
Current-sinking		No
Current-sourcing		Yes
Digital outputs, parameterizable		Yes
Short-circuit protection		Yes
• Response threshold, typ.		1 A; 0.7 to 1.3 A
Open-circuit detection		Yes
Limitation of inductive shutdown voltage to		Typ. L+ (-50 V)
Controlling a digital input		Yes
Switching capacity of the outputs		
• with resistive load, max.		0.5 A
• on lamp load, max.		5 W
Load resistance range		
• lower limit		48 Ω
• upper limit		12 kΩ
Output current		
• for signal "1" rated value		0.5 A
• for signal "0" residual current, max.		0.1 mA
Output delay with resistive load		
• "0" to "1", typ.		50 µs
• "1" to "0", typ.		100 µs
Parallel switching of two outputs		
• for uprating		No
• for redundant control of a load		Yes
Switching frequency		
• with resistive load, max.		100 Hz
• with inductive load, max.		2 Hz
• on lamp load, max.		10 Hz
Total current of the outputs		
• Current per channel, max.		0.5 A
• Current per module, max.		8 A
Total current of the outputs (per module)		
horizontal installation		
— up to 40 °C, max.		8 A
— up to 50 °C, max.		6 A
— up to 60 °C, max.		4 A
vertical installation		
— up to 30 °C, max.		8 A
— up to 40 °C, max.		6 A
— up to 50 °C, max.		4 A
Cable length		
• shielded, max.		1 000 m
• unshielded, max.		600 m
<b>Interrupts/diagnostics/status information</b>		
Diagnostics function		Yes
Substitute values connectable		Yes
Alarms		
• Diagnostic alarm		Yes
Diagnoses		
• Monitoring the supply voltage		Yes
• Wire-break		Yes; Module-wise
• Short-circuit to M		Yes; Module-wise
• Short-circuit to L+		Yes; Module-wise
• Group error		Yes
Diagnostics indication LED		

• Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
• Channel status display	Yes; green LED
• for channel diagnostics	No
• for module diagnostics	Yes; green/red DIAG LED

#### Potential separation

Potential separation channels	
• between the channels	No
• between the channels and backplane bus	Yes

#### Isolation

Isolation tested with	707 V DC (type test)
-----------------------	----------------------

#### Standards, approvals, certificates

Suitable for safety functions	No
Suitable for safety-related tripping of standard modules	Yes; see FAQ Entry ID: 39198632
Highest safety class achievable in safety mode	
• Performance level according to ISO 13849-1	PL d
• SIL acc. to IEC 61508	SIL 2

#### Ambient conditions

Ambient temperature during operation	
• horizontal installation, min.	-30 °C; < 0 °C as of FS03
• horizontal installation, max.	60 °C
• vertical installation, min.	-30 °C; < 0 °C as of FS03
• vertical installation, max.	50 °C

#### Altitude during operation relating to sea level

• Installation altitude above sea level, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
---	--

#### Dimensions

Width	15 mm
Height	73 mm
Depth	58 mm

#### Weights

Weight, approx.	30 g
-----------------	------

**last modified:** 9/27/2021 