



Figure similar

SIMATIC HMI MTP1000, Unified Comfort Panel, touch operation, 10.1" widescreen TFT display, 16 million colors, PROFINET interface, configurable from WinCC Unified Comfort V16, contains open-source software, which is provided free of charge See enclosed Blu-Ray

General information	
Product type designation	MTP1000 Unified Comfort
Display	
Design of display	TFT
Screen diagonal	10.1 in
Display width	217 mm
Display height	135.6 mm
Number of colors	16 777 216
Resolution (pixels)	
• Horizontal image resolution	1 280 pixel
• Vertical image resolution	800 pixel
Backlighting	
• MTBF backlighting (at 25 °C)	50 000 h; At 25°C
• Backlight dimmable	Yes; 5-100 %
Control elements	
Keyboard fonts	
• Numeric keyboard	Yes; Onscreen keyboard
• alphanumeric keyboard	Yes; Onscreen keyboard
Touch operation	
• Design as touch screen	Yes
• Design as multi-touch screen	Yes
Installation type/mounting	
Mounting position	vertical
Mounting in portrait format possible	Yes
Mounting in landscape format possible	Yes
maximum permissible angle of inclination without external ventilation	35°
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	0.5 A
Current consumption, max.	1.1 A
Starting current inrush I <sub>st</sub>	0.5 A <sup>2</sup> ·s
Memory	
Flash	Yes
RAM	Yes

Type of output	
Acoustics	
• Buzzer	Yes
• Speaker	No
Time of day	
Clock	
• Hardware clock (real-time)	Yes
• Software clock	Yes
• retentive	Yes; Back-up duration typically 6 weeks
• synchronizable	Yes
Interfaces	
Number of industrial Ethernet interfaces	2; 2 ports (switch) + independent port
Number of RS 485 interfaces	1; RS 422 / 485 combined
Number of RS 422 interfaces	0; together with RS 485
Number of USB interfaces	4; USB 3.1 Gen. 1 (type A)
Number of SD card slots	2
Industrial Ethernet	
• Industrial Ethernet status LED	2
• Number of ports of the integrated switch	2
Protocols	
PROFINET	Yes
Supports protocol for PROFINET IO	No
Protocols (Ethernet)	
• TCP/IP	Yes
• DHCP	Yes
• SNMP	Yes
• DCP	Yes
• LLDP	Yes
Redundancy mode	
Media redundancy	
— MRP	Yes
EMC	
Emission of radio interference acc. to EN 55 011	
• Limit class A, for use in industrial areas	Yes
• Limit class B, for use in residential areas	No
Degree and class of protection	
IP (at the front)	IP65
IP (rear)	IP20
NEMA (front)	
• Enclosure Type 4x at the front	Yes
• Enclosure Type 12 at the front	No
Standards, approvals, certificates	
CE mark	Yes
cULus	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
Use in hazardous areas	
• ATEX Zone 2	No; Available soon
• ATEX Zone 22	No; Available soon
• IECEx Zone 2	No; Available soon
• IECEx Zone 22	No; Available soon
• cULus Class I Zone 2, Division 2	No; Available soon
• cULus Class II Division 2	No
• FM Class I Division 2	No; Available soon
• FM Class II Division 2	No
Marine approval	
• Germanischer Lloyd (GL)	No; Available soon
• American Bureau of Shipping (ABS)	No; Available soon
• Bureau Veritas (BV)	No; Available soon
• Det Norske Veritas (DNV)	No; Available soon
• Lloyds Register of Shipping (LRS)	No; Available soon

- Nippon Kaiji Kyokai (Class NK) No; Available soon
- Chinese Classification Society (CCS) No; Available soon

### Ambient conditions

Suited for indoor use	Yes
Suited for outdoor use	No

#### Ambient temperature during operation

##### Operation (vertical installation)

- For vertical installation, min. 0 °C
- For vertical installation, max. 50 °C

##### Operation (max. tilt angle)

- At maximum tilt angle, min. 0 °C
- At maximum tilt angle, max. 40 °C

##### Operation (vertical installation, portrait format)

- For vertical installation, min. 0 °C
- For vertical installation, max. 40 °C

##### Operation (max. tilt angle, portrait format)

- At maximum tilt angle, min. 0 °C
- At maximum tilt angle, max. 35 °C

#### Ambient temperature during storage/transportation

- min. -20 °C
- max. 60 °C

#### Relative humidity

- Operation, max. 90 %; no condensation

### Operating systems

proprietary	Yes
-------------	-----

### configuration / header

Message indicator	Yes
Alarm system (incl. buffer and acknowledgment)	Yes
Process value display (output)	Yes
Process value default (input) possible	Yes
Recipe management	Yes

#### Configuration software

- WinCC Unified Comfort Engineering (TIA Portal) Yes
- WinCC Unified PC Engineering (TIA Portal) Yes

### Languages

#### Online languages

- Number of online/runtime languages 32

#### Project languages

- Languages per project 32

### Functionality under WinCC Unified

Libraries	Yes
-----------	-----

#### Applications/options

- Writer Yes
- Web browser Yes
- Media Player Yes
- SIMATIC WinCC Sm@rtServer Yes
- SIMATIC WinCC Audit No
- Unified Collaboration Yes

#### JavaScript

Yes

#### Task planner

- time-controlled Yes
- task-controlled Yes

#### Help system

- Number of characters per info text 70
- Number of message texts per message 10

#### functionality under WinCC Unified / alarm system / header

- Number of alarm classes 32
- Bit messages
  - Number of bit messages 9 000
- Analog messages
  - Number of analog messages 300
- S7 alarm number procedure Yes
- System messages HMI Yes

• System messages, other (SIMATIC S7, Sinumerik, Simotion, etc.)	Yes
• Number of characters per message	512
• Number of process values per message	10
• Acknowledgment groups	Yes
• Message indicator	No
• Message buffer	Yes; Configured as alarm archive
— Circulating buffer	Yes
— retentive	Yes
— maintenance-free	Yes
<b>Parameter set management (recipes)</b>	
• Number of parameter set types	750
• Parameter sets per parameter set type	2 000
• Entries per parameter set	1 000
• Parameter set memory expandable	Yes
<b>functionality under WinCC Unified / variables / header</b>	
• Number of variables per device	8 000
• Number of variables per screen	600
• Limit values	Yes
• Structures	Yes
• Arrays	Yes
<b>functionality under WinCC Unified / screens / header</b>	
• Number of configurable images	1 200
• Faceplate	Yes
<b>Image objects</b>	
• Number of objects per image	800
• Picture window	Yes
• Text fields	Yes
• I/O fields	Yes
• Graphic I/O fields (graphics list)	Yes
• Symbolic I/O fields (text list)	Yes
• Scalable Vector Graphics (SVG)	Yes
• Date/time fields	Yes
• Checkbox	Yes
• Option button	Yes
• Switches	Yes
• Buttons	Yes
• Graphic display	Yes
• Icons	Yes
• Custom web display	Yes
• Geometric objects	Yes
<b>functionality under WinCC Unified / complex screen objects / header</b>	
• Number of complex objects per screen	40
• Alarm view	Yes
• Trend view	Yes
• User view	Yes
• Status/control	No
• Parameter set display	Yes
• HTML browser	Yes
• Bar graphs	Yes
• Sliders	Yes
• Pointer instruments	Yes
• Analog/digital clock	Yes
<b>functionality under WinCC Unified / lists / header</b>	
• Number of text lists per project	750
• Number of entries per text list	750
• Number of graphics lists per project	750
• Number of entries per graphics list	750
<b>functionality under WinCC Unified / archiving / header</b>	
• Number of archives per device	50
• Number of entries per archive	500 000
• Message archive	Yes
• Process value archive	Yes
• type of archiving / for WinCC Unified	

— Sequential archive	Yes
— Short-term archive	Yes
• storage location / of archiving / for WinCC Unified	
— Memory card	Yes
— storage location / of archiving / for WinCC Unified / USB mass storage	Yes
— Ethernet	No
<b>Security</b>	
• Number of roles	50
• Number of function rights	0; V16
• Number of users	200
• Password export/import	Yes
• Central user administration	Yes; as of WinCC V17
<b>functionality under WinCC Unified / transfer (upload/download) / header</b>	
• USB	No
• Ethernet	Yes
• using external storage medium	Yes; as of WinCC Unified V17
<b>Process coupling</b>	
• S7-1200	Yes
• S7-1500	Yes
• S7-200	No
• S7-300/400	Yes
• Number of S7 connections	16
• LOGO!	No
• SIMOTION	No
• OPC UA Client	Yes
• OPC UA Server	Yes
• Software Controller/Open Controller	No
<b>functionality under WinCC Unified / service tools/configuration tools / header</b>	
• Backup/Restore manually	Yes
• Backup/Restore automatically	Yes
• Simulation	Yes
• Device switchover	Yes
<b>Peripherals/Options</b>	
Peripherals	Printer, barcode reader
Printer	Yes
SIMATIC HMI MM memory card: Multi Media Card	No
SIMATIC HMI SD memory card: Secure Digital memory card	Yes
SIMATIC HMI CF memory card Compact Flash Card	No
USB memory	Yes
SIMATIC IPC USB Flashdrive (USB stick)	Yes
SIMATIC HMI USB stick	Yes
Network camera	No
<b>Mechanics/material</b>	
Enclosure material (front)	
• Aluminum	Yes
<b>Dimensions</b>	
Width of the housing front	280 mm
Height of housing front	205 mm
Mounting cutout, width	264 mm
Mounting cutout, height	189 mm
Overall depth	64 mm
<b>Weights</b>	
Weight (without packaging)	2.1 kg
<b>last modified:</b>	4/1/2022 