

SIMATIC S7-1500F, CPU 1516F-3 PN/DP, central processing unit with work memory 3 MB for program and 7.5 MB for data 1st interface: PROFINET IRT with 2-port switch, 2nd interface: PROFINET RT, 3rd interface: PROFIBUS, 6 ns bit performance, SIMATIC Memory Card required \*\*\*\*approvals and certificates according to entry 109817466 at support.industry.siemens.com to be considered!  
\*\*\*

| General information  |   |
|--|---|
| Product type designation   | CPU 1516F-3 PN/DP   |
| HW functional status   | FS01  |
| Firmware version   | V3.0  |
| <ul style="list-style-type: none"> <li>FW update possible</li> </ul>                                     | Yes   |
| Product function   |   |
| <ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>   | Yes; I&M0 to I&M3   |
| <ul style="list-style-type: none"> <li>Isochronous mode</li> </ul>                                       | Yes; Distributed and central; with minimum OB 6x cycle of 375 µs (distributed) and 1 ms (central) |
| Engineering with   |   |
| <ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul> | V18 (FW V3.0); with older TIA Portal versions configurable as 6ES7516-3FN02-0AB0                  |
| Configuration control  |   |
| via dataset  | Yes   |
| Display  |   |
| Screen diagonal [cm]   | 6.1 cm  |
| Control elements   |   |
| Number of keys   | 8   |
| Mode buttons   | 2   |
| Supply voltage   |   |
| Rated value (DC)   | 24 V  |
| permissible range, lower limit (DC)  | 19.2 V  |
| permissible range, upper limit (DC)  | 28.8 V  |
| Reverse polarity protection  | Yes   |
| Mains buffering  |   |
| <ul style="list-style-type: none"> <li>Mains/voltage failure stored energy time</li> </ul>               | 5 ms  |
| <ul style="list-style-type: none"> <li>Repeat rate, min.</li> </ul>                                      | 1/s   |
| Input current  |   |
| Current consumption (rated value)  | 0.87 A  |
| Current consumption, max.  | 1.08 A  |
| Inrush current, max.   | 1.15 A; Rated value   |
| I <sup>2</sup> t   | 0.6 A <sup>2</sup> ·s   |
| Power  |   |
| Infeed power to the backplane bus  | 12 W  |
| Power consumption from the backplane bus (balanced)  | 6.7 W   |
| Power loss   |   |
| Power loss, typ.   | 4 W   |
| Memory   |   |
| Number of slots for SIMATIC memory card  | 1   |
| SIMATIC memory card required   | Yes   |
| Work memory  |   |
| <ul style="list-style-type: none"> <li>integrated (for program)</li> </ul>                               | 3 Mbyte   |
| <ul style="list-style-type: none"> <li>integrated (for data)</li> </ul>                                  | 7.5 Mbyte   |
| Load memory  |   |
| <ul style="list-style-type: none"> <li>Plug-in (SIMATIC Memory Card), max.</li> </ul>                    | 32 Gbyte  |
| Backup   |   |
| <ul style="list-style-type: none"> <li>maintenance-free</li> </ul>                                       | Yes   |
| CPU processing times   |   |

|  |   |
|--|---|
| for bit operations, typ.   | 6 ns  |
| for word operations, typ.  | 7 ns  |
| for fixed point arithmetic, typ.                                   | 9 ns  |
| for floating point arithmetic, typ.                                | 37 ns   |
| <b>CPU-blocks</b>  |   |
| Number of elements (total)   | 8 000; Blocks (OB, FB, FC, DB) and UDTs   |
| <b>DB</b>  |   |
| • Number range   | 1 ... 60 999; subdivided into: number range that can be used by the user: 1 ... 59 999, and number range of DBs created via SFC 86: 60 000 ... 60 999 |
| • Size, max.   | 7.5 Mbyte; For DBs with absolute addressing, the max. size is 64 KB   |
| <b>FB</b>  |   |
| • Number range   | 0 ... 65 535  |
| • Size, max.   | 1 Mbyte   |
| <b>FC</b>  |   |
| • Number range   | 0 ... 65 535  |
| • Size, max.   | 1 Mbyte   |
| <b>OB</b>  |   |
| • Size, max.   | 1 Mbyte   |
| • Number of free cycle OBs   | 100   |
| • Number of time alarm OBs   | 20  |
| • Number of delay alarm OBs  | 20  |
| • Number of cyclic interrupt OBs                                   | 20; With minimum OB 3x cycle of 250 µs  |
| • Number of process alarm OBs                                      | 50  |
| • Number of DPV1 alarm OBs   | 3   |
| • Number of isochronous mode OBs                                   | 3   |
| • Number of technology synchronous alarm OBs                       | 2   |
| • Number of startup OBs  | 100   |
| • Number of asynchronous error OBs                                 | 4   |
| • Number of synchronous error OBs                                  | 2   |
| • Number of diagnostic alarm OBs                                   | 1   |
| <b>Nesting depth</b>   |   |
| • per priority class   | 24; Up to 8 possible for F-blocks   |
| <b>Counters, timers and their retentivity</b>                      |   |
| <b>S7 counter</b>  |   |
| • Number   | 2 048   |
| <b>Retentivity</b>   |   |
| — adjustable   | Yes   |
| <b>IEC counter</b>   |   |
| • Number   | Any (only limited by the main memory)   |
| <b>Retentivity</b>   |   |
| — adjustable   | Yes   |
| <b>S7 times</b>  |   |
| • Number   | 2 048   |
| <b>Retentivity</b>   |   |
| — adjustable   | Yes   |
| <b>IEC timer</b>   |   |
| • Number   | Any (only limited by the main memory)   |
| <b>Retentivity</b>   |   |
| — adjustable   | Yes   |
| <b>Data areas and their retentivity</b>                            |   |
| Retentive data area (incl. timers, counters, flags), max.          | 512 kbyte; In total; available retentive memory for bit memories, timers, counters, DBs, and technology data (axes): 472 KB                           |
| Extended retentive data area (incl. timers, counters, flags), max. | 7.5 Mbyte; When using PS 6 0W 24/48/60 V DC HF  |
| <b>Flag</b>  |   |
| • Size, max.   | 16 kbyte  |
| • Number of clock memories   | 8; 8 clock memory bit, grouped into one clock memory byte   |
| <b>Data blocks</b>   |   |
| • Retentivity adjustable   | Yes   |
| • Retentivity preset   | No  |
| <b>Local data</b>  |   |
| • per priority class, max.   | 64 kbyte; max. 16 KB per block  |

| Address area                        |   |
|-------------------------------------|---|
| Number of IO modules                | 8 192; max. number of modules / submodules  |
| I/O address area                    |   |
| • Inputs                            | 32 kbyte; All inputs are in the process image   |
| • Outputs                           | 32 kbyte; All outputs are in the process image  |
| per integrated IO subsystem         |   |
| — Inputs (volume)                   | 8 kbyte   |
| — Outputs (volume)                  | 8 kbyte   |
| per CM/CP                           |   |
| — Inputs (volume)                   | 8 kbyte   |
| — Outputs (volume)                  | 8 kbyte   |
| Subprocess images                   |   |
| • Number of subprocess images, max. | 32  |
| Hardware configuration              |   |
| Number of distributed IO systems    | 64; A distributed I/O system is characterized not only by the integration of distributed I/O via PROFINET or PROFIBUS communication modules, but also by the connection of I/O via AS-i master modules or links (e.g. IE/PB-Link) |
| Number of DP masters                |   |
| • integrated                        | 1   |
| • Via CM                            | 8; A maximum of 8 CMs/CPs (PROFIBUS, PROFINET, Ethernet) can be inserted in total   |
| Number of IO Controllers            |   |
| • integrated                        | 2   |
| • Via CM                            | 8; A maximum of 8 CMs/CPs (PROFIBUS, PROFINET, Ethernet) can be inserted in total   |
| Rack                                |   |
| • Modules per rack, max.            | 32; CPU + 31 modules  |
| • Number of lines, max.             | 1   |
| PtP CM                              |   |
| • Number of PtP CMs                 | the number of connectable PtP CMs is only limited by the number of available slots  |
| Time of day                         |   |
| Clock                               |   |
| • Type                              | Hardware clock  |
| • Backup time                       | 6 wk; At 40 °C ambient temperature, typically   |
| • Deviation per day, max.           | 10 s; Typ.: 2 s   |
| Operating hours counter             |   |
| • Number                            | 16  |
| Clock synchronization               |   |
| • supported                         | Yes   |
| • to DP, master                     | Yes   |
| • in AS, master                     | Yes   |
| • in AS, slave                      | Yes   |
| • on Ethernet via NTP               | Yes   |
| Interfaces                          |   |
| Number of PROFINET interfaces       | 2   |
| Number of PROFIBUS interfaces       | 1   |
| 1. Interface                        |   |
| Interface types                     |   |
| • RJ 45 (Ethernet)                  | Yes; X1   |
| • Number of ports                   | 2   |
| • integrated switch                 | Yes   |
| Protocols                           |   |
| • IP protocol                       | Yes; IPv4   |
| • PROFINET IO Controller            | Yes   |
| • PROFINET IO Device                | Yes   |
| • SIMATIC communication             | Yes   |
| • Open IE communication             | Yes; Optionally also encrypted  |
| • Web server                        | Yes   |
| • Media redundancy                  | Yes   |
| PROFINET IO Controller              |   |
| Services                            |   |

|   |  |
|---|--|
| — PG/OP communication   | Yes  |
| — Isochronous mode  | Yes  |
| — Direct data exchange  | Yes; Requirement: IRT and isochronous mode (MRPD optional)   |
| — IRT   | Yes  |
| — PROFINergy  | Yes; per user program  |
| — Prioritized startup   | Yes; Max. 32 PROFINET devices  |
| — Number of connectable IO Devices, max.                                      | 256; In total, up to 1 000 distributed I/O devices can be connected via AS-i, PROFIBUS or PROFINET   |
| — Of which IO devices with IRT, max.  | 64   |
| — Number of connectable IO Devices for RT, max.                               | 256  |
| — of which in line, max.  | 256  |
| — Number of IO Devices that can be simultaneously activated/deactivated, max. | 8; in total across all interfaces  |
| — Number of IO Devices per tool, max.   | 8  |
| — Updating times  | The minimum value of the update time also depends on communication share set for PROFINET IO, on the number of IO devices, and on the quantity of configured user data |
| <b>Update time for IRT</b>  |  |
| — for send cycle of 250 µs  | 250 µs to 4 ms; Note: In the case of IRT with isochronous mode, the minimum update time of 375 µs of the isochronous OB is decisive                                    |
| — for send cycle of 500 µs  | 500 µs to 8 ms   |
| — for send cycle of 1 ms  | 1 ms to 16 ms  |
| — for send cycle of 2 ms  | 2 ms to 32 ms  |
| — for send cycle of 4 ms  | 4 ms to 64 ms  |
| — With IRT and parameterization of "odd" send cycles                          | Update time = set "odd" send clock (any multiple of 125 µs: 375 µs, 625 µs ... 3 875 µs)   |
| <b>Update time for RT</b>   |  |
| — for send cycle of 250 µs  | 250 µs to 128 ms   |
| — for send cycle of 500 µs  | 500 µs to 256 ms   |
| — for send cycle of 1 ms  | 1 ms to 512 ms   |
| — for send cycle of 2 ms  | 2 ms to 512 ms   |
| — for send cycle of 4 ms  | 4 ms to 512 ms   |
| <b>PROFINET IO Device</b>   |  |
| <b>Services</b>   |  |
| — PG/OP communication   | Yes  |
| — Isochronous mode  | No   |
| — IRT   | Yes  |
| — PROFINergy  | Yes; per user program  |
| — Shared device   | Yes  |
| — Number of IO Controllers with shared device, max.                           | 4  |
| — activation/deactivation of I-devices  | Yes; per user program  |
| — Asset management record   | Yes; per user program  |
| <b>2. Interface</b>   |  |
| <b>Interface types</b>  |  |
| ● RJ 45 (Ethernet)  | Yes; X2  |
| ● Number of ports   | 1  |
| ● integrated switch   | No   |
| <b>Protocols</b>  |  |
| ● IP protocol   | Yes; IPv4  |
| ● PROFINET IO Controller  | Yes  |
| ● PROFINET IO Device  | Yes  |
| ● SIMATIC communication   | Yes  |
| ● Open IE communication   | Yes; Optionally also encrypted   |
| ● Web server  | Yes  |
| ● Media redundancy  | No   |
| <b>PROFINET IO Controller</b>   |  |
| <b>Services</b>   |  |
| — PG/OP communication   | Yes  |
| — Isochronous mode  | No   |
| — Direct data exchange  | No   |
| — IRT   | No   |
| — PROFINergy  | Yes; per user program  |

|   |  |
|---|--|
| — Prioritized startup   | No   |
| — Number of connectable IO Devices, max.                                      | 32; In total, up to 1 000 distributed I/O devices can be connected via AS-i, PROFIBUS or PROFINET  |
| — Number of connectable IO Devices for RT, max.                               | 32   |
| — of which in line, max.  | 32   |
| — Number of IO Devices that can be simultaneously activated/deactivated, max. | 8; in total across all interfaces  |
| — Number of IO Devices per tool, max.   | 8  |
| — Updating times  | The minimum value of the update time also depends on communication share set for PROFINET IO, on the number of IO devices, and on the quantity of configured user data |
| <b>Update time for RT</b>   |  |
| — for send cycle of 1 ms  | 1 ms to 512 ms   |
| <b>PROFINET IO Device</b>   |  |
| <b>Services</b>   |  |
| — PG/OP communication   | Yes  |
| — Isochronous mode  | No   |
| — IRT   | No   |
| — PROFenergy  | Yes; per user program  |
| — Prioritized startup   | No   |
| — Shared device   | Yes  |
| — Number of IO Controllers with shared device, max.                           | 4  |
| — activation/deactivation of I-devices  | Yes; per user program  |
| — Asset management record   | Yes; per user program  |
| <b>3. Interface</b>   |  |
| <b>Interface types</b>  |  |
| • RS 485  | Yes; X3  |
| • Number of ports   | 1  |
| <b>Protocols</b>  |  |
| • PROFIBUS DP master  | Yes  |
| • PROFIBUS DP slave   | No   |
| • SIMATIC communication   | Yes  |
| <b>PROFIBUS DP master</b>   |  |
| • Number of connections, max.   | 48; for the integrated PROFIBUS DP interface   |
| • Number of DP slaves, max.   | 125; In total, up to 1 000 distributed I/O devices can be connected via AS-i, PROFIBUS or PROFINET   |
| <b>Services</b>   |  |
| — PG/OP communication   | Yes  |
| — Equidistance  | Yes  |
| — Isochronous mode  | Yes  |
| — Activation/deactivation of DP slaves  | Yes  |
| <b>Interface types</b>  |  |
| <b>RJ 45 (Ethernet)</b>   |  |
| • 100 Mbps  | Yes  |
| • Autonegotiation   | Yes  |
| • Autocrossing  | Yes  |
| • Industrial Ethernet status LED  | Yes  |
| <b>RS 485</b>   |  |
| • Transmission rate, max.   | 12 Mbit/s  |
| <b>Protocols</b>  |  |
| PROFIsafe   | Yes; V2.4 / V2.6   |
| <b>Number of connections</b>  |  |
| • Number of connections, max.   | 256; via integrated interfaces of the CPU and connected CPs / CMs  |
| • Number of connections reserved for ES/HMI/web                               | 10   |
| • Number of connections via integrated interfaces                             | 128  |
| • Number of S7 routing paths  | 16   |
| <b>Redundancy mode</b>  |  |
| • H-Sync forwarding   | Yes  |
| <b>Media redundancy</b>   |  |
| — Media redundancy  | only via 1st interface (X1)  |
| — MRP   | Yes; MRP Automanager according to IEC 62439-2 Edition 2.0, MRP Manager; MRP Client   |

|  |  |
|--|--|
| — MRP interconnection, supported       | Yes; as MRP ring node according to IEC 62439-2 Edition 3.0 |
| — MRPD                                 | Yes; Requirement: IRT                                      |
| — Switchover time on line break, typ.  | 200 ms; For MRP, bumpless for MRPD                         |
| — Number of stations in the ring, max. | 50   |

#### SIMATIC communication

|                               |  |
|-------------------------------|--|
| • PG/OP communication         | Yes; encryption with TLS V1.3 pre-selected         |
| • S7 routing                  | Yes  |
| • Data record routing         | Yes  |
| • S7 communication, as server | Yes  |
| • S7 communication, as client | Yes  |
| • User data per job, max.     | See online help (S7 communication, user data size) |

#### Open IE communication

|   |  |
|---|--|
| • TCP/IP  | Yes                                    |
| — Data length, max.                               | 64 kbyte                               |
| — several passive connections per port, supported | Yes                                    |
| • ISO-on-TCP (RFC1006)                            | Yes                                    |
| — Data length, max.                               | 64 kbyte                               |
| • UDP   | Yes                                    |
| — Data length, max.                               | 2 kbyte; 1 472 bytes for UDP broadcast |
| — UDP multicast                                   | Yes; max. 118 multicast circuits       |
| • DHCP  | Yes                                    |
| • DNS   | Yes                                    |
| • SNMP  | Yes                                    |
| • DCP   | Yes                                    |
| • LLDP  | Yes                                    |
| • Encryption                                      | Yes; Optional                          |

#### Web server

|         |                              |
|---------|------------------------------|
| • HTTP  | Yes; Standard and user pages |
| • HTTPS | Yes; Standard and user pages |

#### OPC UA

|  |  |
|--|--|
| • Runtime license required   | Yes; "Medium" license required   |
| • OPC UA Client  | Yes; Data Access (registered Read/Write), Method Call  |
| — Application authentication   | Yes  |
| — Security policies  | Available security policies: None, Basic128Rsa15, Basic256Rsa15, Basic256Sha256  |
| — User authentication  | "anonymous" or by user name & password   |
| — Number of connections, max.  | 10   |
| — Number of nodes of the client interfaces, recommended max.   | 2 000  |
| — Number of elements for one call of OPC-UA_NodeGetHandleList/OPC-UA_ReadList/OPC-UA_WriteList, max.   | 300  |
| — Number of elements for one call of OPC-UA_NameSpaceGetIndexList, max.                                | 20   |
| — Number of elements for one call of OPC-UA_MethodGetHandleList, max.                                  | 100  |
| — Number of simultaneous calls of the client instructions for session management, per connection, max. | 1  |
| — Number of simultaneous calls of the client instructions for data access, per connection, max.        | 5  |
| — Number of registerable nodes, max.   | 5 000  |
| — Number of registerable method calls of OPC-UA_MethodCall, max.                                       | 100  |
| — Number of inputs/outputs when calling OPC-UA_MethodCall, max.  | 20   |
| • OPC UA Server  | Yes; Data Access (Read, Write, Subscribe), Method Call, Alarms & Condition (A&C), Custom Address Space                   |
| — Application authentication   | Yes  |
| — Security policies  | available security policies: None, Basic128Rsa15, Basic256Rsa15, Basic256Sha256, Aes128Sha256RsaOaep, Aes256Sha256RsaPss |
| — User authentication  | "anonymous" or by user name & password   |
| — GDS support (certificate management)   | Yes  |
| — Number of sessions, max.   | 48   |
| — Number of accessible variables, max.   | 100 000  |

|   |   |
|---|---|
| — Number of registerable nodes, max.                                  | 20 000  |
| — Number of subscriptions per session, max.                           | 50  |
| — Sampling interval, min.   | 100 ms  |
| — Publishing interval, min.   | 100 ms  |
| — Number of server methods, max.                                      | 50  |
| — Number of inputs/outputs per server method, max.                    | 20  |
| — Number of monitored items, recommended max.                         | 4 000; for 1 s sampling interval and 1 s send interval  |
| — Number of server interfaces, max.                                   | 10 of each "Server interfaces" / "Companion specification" type and 20 of the type "Reference namespace"                          |
| — Number of nodes for user-defined server interfaces, max.            | 30 000  |
| • Alarms and Conditions   | Yes   |
| — Number of program alarms  | 200   |
| — Number of alarms for system diagnostics                             | 100   |
| <b>Further protocols</b>  |   |
| • MODBUS  | Yes; MODBUS TCP   |
| <b>Isochronous mode</b>   |   |
| Equidistance  | Yes   |
| <b>S7 message functions</b>   |   |
| Number of login stations for message functions, max.                  | 64  |
| Program alarms  | Yes   |
| Number of configurable program messages, max.                         | 10 000; Program messages are generated by the "Program_Alarm" block, ProDiag or GRAPH   |
| Number of loadable program messages in RUN, max.                      | 5 000   |
| Number of simultaneously active program alarms                        |   |
| • Number of program alarms  | 1 000   |
| • Number of alarms for system diagnostics                             | 200   |
| • Number of alarms for motion technology objects                      | 160   |
| <b>Test commissioning functions</b>                                   |   |
| Joint commission (Team Engineering)                                   | Yes; Parallel online access possible for up to 8 engineering systems  |
| Status block  | Yes; Up to 8 simultaneously (in total across all ES clients)  |
| Single step   | No  |
| Number of breakpoints   | 8   |
| <b>Status/control</b>   |   |
| • Status/control variable   | Yes; without fail-safe  |
| • Variables   | inputs/outputs, bit memories, DBs, peripheral I/Os (without fail-safe), times, counters   |
| • Number of variables, max.   |   |
| — of which status variables, max.                                     | 200; per job  |
| — of which control variables, max.                                    | 200; per job  |
| <b>Forcing</b>  |   |
| • Forcing   | Yes; without fail-safe  |
| • Forcing, variables  | peripheral inputs/outputs (without fail-safe)   |
| • Number of variables, max.   | 200   |
| <b>Diagnostic buffer</b>  |   |
| • present   | Yes   |
| • Number of entries, max.   | 3 200   |
| — of which powerfail-proof  | 500   |
| <b>Traces</b>   |   |
| • Number of configurable Traces                                       | 4; Up to 512 KB of data per trace are possible  |
| <b>Interrupts/diagnostics/status information</b>                      |   |
| <b>Diagnostics indication LED</b>                                     |   |
| • RUN/STOP LED  | Yes   |
| • ERROR LED   | Yes   |
| • MAINT LED   | Yes   |
| • STOP ACTIVE LED   | Yes   |
| • Connection display LINK TX/RX                                       | Yes   |
| <b>Supported technology objects</b>                                   |   |
| Motion Control  | Yes; Note: The number of technology objects affects the cycle time of the PLC program; selection guide via the TIA Selection Tool |
| • Number of available Motion Control resources for technology objects | 2 400   |

|  |   |
|--|---|
| <ul style="list-style-type: none"> <li>Required Motion Control resources <ul style="list-style-type: none"> <li>per speed-controlled axis</li> <li>per positioning axis</li> <li>per synchronous axis</li> <li>per external encoder</li> <li>per output cam</li> <li>per cam track</li> <li>per probe</li> </ul> </li> <li>Positioning axis <ul style="list-style-type: none"> <li>Number of positioning axes at motion control cycle of 4 ms (typical value)</li> <li>Number of positioning axes at motion control cycle of 8 ms (typical value)</li> </ul> </li> </ul> | <p>40</p> <p>80</p> <p>160</p> <p>80</p> <p>20</p> <p>160</p> <p>40</p> <p>11</p> <p>20</p>   |
| <p>Controller</p> <ul style="list-style-type: none"> <li>PID_Compact</li> <li>PID_3Step</li> <li>PID-Temp</li> </ul>   | <p>Yes; Universal PID controller with integrated optimization</p> <p>Yes; PID controller with integrated optimization for valves</p> <p>Yes; PID controller with integrated optimization for temperature</p>  |
| <p>Counting and measuring</p> <ul style="list-style-type: none"> <li>High-speed counter</li> </ul>   | <p>Yes</p>  |
| <b>Standards, approvals, certificates</b>  |   |
| Highest safety class achievable in safety mode   |   |
| <ul style="list-style-type: none"> <li>Performance level according to ISO 13849-1</li> <li>SIL acc. to IEC 61508</li> </ul>  | <p>PLe</p> <p>SIL 3</p>   |
| Probability of failure (for service life of 20 years and repair time of 100 hours)   |   |
| <ul style="list-style-type: none"> <li>Low demand mode: PFDavg in accordance with SIL3</li> <li>High demand/continuous mode: PFH in accordance with SIL3</li> </ul>  | <p>&lt; 2.00E-05</p> <p>&lt; 1.00E-09</p>   |
| <b>Ambient conditions</b>  |   |
| Ambient temperature during operation   |   |
| <ul style="list-style-type: none"> <li>horizontal installation, min.</li> <li>horizontal installation, max.</li> <li>vertical installation, min.</li> <li>vertical installation, max.</li> </ul>   | <p>-30 °C; No condensation</p> <p>60 °C; Display: 50 °C, at an operating temperature of typically 50 °C, the display is switched off</p> <p>-30 °C; No condensation</p> <p>40 °C; Display: 40 °C, at an operating temperature of typically 40 °C, the display is switched off</p> |
| Ambient temperature during storage/transportation  |   |
| <ul style="list-style-type: none"> <li>min.</li> <li>max.</li> </ul>   | <p>-40 °C</p> <p>70 °C</p>  |
| Altitude during operation relating to sea level  |   |
| <ul style="list-style-type: none"> <li>Installation altitude above sea level, max.</li> </ul>  | <p>5 000 m; Restrictions for installation altitudes &gt; 2 000 m, see manual</p>  |
| <b>configuration / header</b>  |   |
| configuration / programming / header   |   |
| Programming language   |   |
| <ul style="list-style-type: none"> <li>LAD</li> <li>FBD</li> <li>STL</li> <li>SCL</li> <li>GRAPH</li> </ul>  | <p>Yes; incl. failsafe</p> <p>Yes; incl. failsafe</p> <p>Yes</p> <p>Yes</p> <p>Yes</p>  |
| Know-how protection  |   |
| <ul style="list-style-type: none"> <li>User program protection/password protection</li> <li>Copy protection</li> <li>Block protection</li> </ul>   | <p>Yes</p> <p>Yes</p> <p>Yes</p>  |
| Access protection  |   |
| <ul style="list-style-type: none"> <li>protection of confidential configuration data</li> <li>Password for display</li> <li>Protection level: Write protection</li> <li>Protection level: Read/write protection</li> <li>Protection level: Write protection for Failsafe</li> <li>Protection level: Complete protection</li> </ul>   | <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p>   |
| programming / cycle time monitoring / header   |   |
| <ul style="list-style-type: none"> <li>lower limit</li> </ul>  | <p>adjustable minimum cycle time</p>  |

• upper limit

adjustable maximum cycle time

#### Dimensions

|        |        |
|--------|--------|
| Width  | 70 mm  |
| Height | 147 mm |
| Depth  | 129 mm |

#### Weights

|                 |       |
|-----------------|-------|
| Weight, approx. | 469 g |
|-----------------|-------|

**last modified:**

3/12/2024 