



Figure similar

SIMATIC SD memory card 512 MB Secure Digital card for For devices with corresponding Slot Further information, Quantity and content: see technical data all other HMI panels with SD/MMC slot

General information	
Product type designation	SD memory card
Control elements	
Frame size/design	
<ul style="list-style-type: none"> <li>Standard</li> <li>Flat</li> </ul>	Yes; Typically 10 000 insertion cycles Yes
Installation type/mounting	
Mounting position	Any, dependent on target device
Mounting in portrait format possible	Yes
Mounting in landscape format possible	Yes
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	3.3 V; Max 3.6 V
Input current	
Current consumption (rated value)	100 mA; Typical, maximum value
Memory	
Type of memory	Secure Digital memory card
Memory size	512 Mbyte
Transmission rate for reading, max.	1.6 Mbit/s; Minimum, typical for newly formatted memory
Transmission rate for writing, max.	1.6 Mbit/s; Minimum, typical for newly formatted memory
Wear leveling (distributed writing)	Yes; > 100 000 write/read cycles per cell and > 3 000 000 write/read cycles per card
Write protection switch	Yes; Effectiveness depends on the device
Interfaces	
Device-side interface	
<ul style="list-style-type: none"> <li>Number of pins device-side</li> </ul>	9
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes
cULus	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
RoHS conformity	Yes
China RoHS compliance	Yes
Marine approval	Yes; Passive component, therefore dependent on target device
Use in hazardous areas	
<ul style="list-style-type: none"> <li>ATEX Zone 2</li> <li>ATEX Zone 22</li> <li>IECEx Zone 2</li> </ul>	Yes; Always comply with the operating instructions of the target device. Yes; Always comply with the operating instructions of the target device. Yes; Always comply with the operating instructions of the target device.

<ul style="list-style-type: none"> <li>• IECEx Zone 22</li> <li>• cULus Class I Zone 2, Division 2</li> <li>• FM Class I Division 2</li> </ul>	<p>Yes; Always comply with the operating instructions of the target device.</p> <p>Yes; Always comply with the operating instructions of the target device.</p> <p>Yes; Always comply with the operating instructions of the target device.</p>
<b>Marine approval</b>	
<ul style="list-style-type: none"> <li>• Germanischer Lloyd (GL)</li> <li>• American Bureau of Shipping (ABS)</li> <li>• Bureau Veritas (BV)</li> <li>• Det Norske Veritas (DNV)</li> <li>• Lloyds Register of Shipping (LRS)</li> <li>• Nippon Kaiji Kyokai (Class NK)</li> <li>• Polski Rejestr Statkow (PRS)</li> <li>• Chinese Classification Society (CCS)</li> <li>• Compass working clearance</li> </ul>	<p>Yes; Always comply with the operating instructions of the target device.</p> <p>Yes; Always comply with the operating instructions of the target device.</p> <p>Yes; Always comply with the operating instructions of the target device.</p> <p>Yes; Always comply with the operating instructions of the target device.</p> <p>Yes; Always comply with the operating instructions of the target device.</p> <p>Yes; Always comply with the operating instructions of the target device.</p> <p>Yes; Always comply with the operating instructions of the target device.</p> <p>Yes; Always comply with the operating instructions of the target device.</p> <p>5 m</p>
<b>Ambient conditions</b>	
Suited for indoor use	Yes
Suited for outdoor use	No
<b>Ambient temperature during operation</b>	
<ul style="list-style-type: none"> <li>• min.</li> <li>• max.</li> </ul>	<p>0 °C; Indoor</p> <p>50 °C; Indoor</p>
<b>Ambient temperature during storage/transportation</b>	
<ul style="list-style-type: none"> <li>• min.</li> <li>• max.</li> </ul>	<p>-20 °C</p> <p>60 °C</p>
<b>Relative humidity</b>	
<ul style="list-style-type: none"> <li>• Operation, max.</li> <li>• Condensation permissible</li> </ul>	<p>90 %</p> <p>No; Condensation not permissible</p>
<b>Operating systems</b>	
<b>Runs under operating system</b>	
<ul style="list-style-type: none"> <li>• Windows CE</li> <li>• Windows Vista</li> <li>• Windows XP</li> <li>• Windows 7</li> <li>• Windows 8</li> <li>• Windows 10</li> <li>• Linux</li> <li>• other</li> </ul>	<p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>No</p> <p>Yes; Card must not be formatted!</p>
<b>Mechanics/material</b>	
Enclosure material (front)	
<ul style="list-style-type: none"> <li>• Plastic</li> </ul>	Yes; Gold contacts
Enclosure color (front)	RAL 6034 (color deviation possible)
<b>Service life</b>	
<ul style="list-style-type: none"> <li>• Number of operating cycles, keys</li> </ul>	10; Min. data storage without loss (in years)
<b>Dimensions</b>	
Width	24 mm
Height	32 mm
Thickness	2.1 mm
<b>Weights</b>	
Weight (without packaging)	3 g
Weight (with packaging)	6 g
<b>Scope of supply</b>	
Delivery quantity in pieces	1
<b>Other</b>	
Merchandise	No
Manufacturer name	SIEMENS AG
Manufacturer's address	Gleiwitzerstraße 555, 90475 Nuremberg, Germany
Target devices	for MP177, MP277, MP377 and Mobile Panel 277, WinCC flexible 2008 SP1 and higher for OP77, TP/OP177, TP/OP277, Mobile Panel 177, with SD/MMC slot
Note:	MP377 only up to and including FS:04 or ES:04 - Alternatively 2 GB SD card
<b>Usable in the following products</b>	
<ul style="list-style-type: none"> <li>• Product 1</li> <li>• Product 2</li> </ul>	<p><a href="#">6AV6642-0EA01-3AX0</a></p> <p>6AV6643-0C*</p>

- Product 3
- Product 4
- Product 5
- Product 6
- Product 8
- Product 9
- Product 10
- Product 11
- Product 12
- Product 13
- Product 14
- Product 15
- Product 16
- Product 17
- Product 18
- Product 19

6AV6643-0D\*  
6AV6643-7D\*  
6AV6643-7C\*  
6AV6643-8\*  
[6AV6645-0BE02-0AX0](#)  
6AV6645-0C\*  
6AV6645-0D\*  
6AV6645-0E\*  
6AV6645-0F\*  
6AV6645-0G\*  
6AV6641-0B\*  
6AV6641-0C\*  
6AV6642-0\*  
[6AV6643-0AA01-1AX0](#)  
[6AV6643-0BA01-1AX0](#)  
6AV6643-7BA\*

last modified:

1/15/2021 