



SIMOTION Drive-based Control Unit D410-2 DP/PN; programmable single-axis motion controller with multi-axis option; interfaces: 5 DI, 8 DI/DO, 3 F-DI, 1 F-DO, 1 AI, 1 encoder, 1 DRIVE-CLiQ, 1 PROFIBUS, 2 PROFINET ports, 1 ethernet Note: requires at least SCOUT/firmware V4.3 SP1 HF3

product brand name	SIMOTION
product type designation	D410-2 DP/PN
Version of the motion control system	Single-axis system with multi-axis option

PLC and motion control performance

number of axes / maximum	8
Minimum PROFIBUS cycle clock	1 ms
Minimum PROFINET send cycle clock	0.25 ms
Minimum interpolator cycle clock	0.5 ms
Minimum servo cycle clock	0.5 ms
<ul style="list-style-type: none"> note 	1 ms when using the TO axis and the integrated closed-loop drive control

Integrated drive control / header

Maximum number of axes for integrated drive control	
<ul style="list-style-type: none"> servo 	1
<ul style="list-style-type: none"> vector 	1
<ul style="list-style-type: none"> V/f 	1
<ul style="list-style-type: none"> note 	Alternative control modes; drive control based on SINAMICS S120 CU310-2, firmware version V4.x/V5.x

Memory

RAM (work memory)	122 Mbyte
Additional RAM work memory for Java applications	20 Mbyte
RAM disk (load memory)	60 Mbyte
Retentive memory	108 kbyte
Persistent memory (user data on CF)	1.5 Gbyte

Communication

Interfaces	
<ul style="list-style-type: none"> DRIVE-CLiQ 	1
<ul style="list-style-type: none"> Industrial Ethernet 	1
<ul style="list-style-type: none"> PROFIBUS 	1
<ul style="list-style-type: none"> — note 	Equidistant and isochronous; Can be configured as master or slave
<ul style="list-style-type: none"> PROFINET 	1
<ul style="list-style-type: none"> — note 	Interface with 2 ports; supports PROFINET IO with IRT and RT; configurable as PROFINET IO Controller and/or Device; supports media redundancy (MRP and MRPD)

General technical data

Fan	Integrated
DC supply voltage	
<ul style="list-style-type: none"> rated value 	24 V
<ul style="list-style-type: none"> minimum 	20.4 V
<ul style="list-style-type: none"> maximum 	28.8 V
consumed current / typical	800 mA
<ul style="list-style-type: none"> note 	with no load on inputs/outputs. no 24 V supply via DRIVE-CLiQ and

Making current, typ.	PROFIBUS interface 3 A
Power loss, typ.	20 W
Ambient temperature, during	
• long-term storage	-25 ... +55 °C
• transport	-40 ... +70 °C
• operation	0 ... 55 °C
— note	Maximum installation altitude 4000 m (13124 ft) above sea level. Above an altitude of 2000 m (6562 ft), the maximum ambient temperature decreases by 7 °C (12.6 °F) per 1000 m (3281 ft).
Relative humidity	
• during operation	5 ... 95 %
• without condensation, tested acc. to IEC 60068-2-38	Wert fehlt
Air pressure	620 ... 1 060 hPa
Degree of protection	IP20 / UL open type
height	190.7 mm
width	73 mm
• depth	74.4 mm
net weight	830 g

Digital inputs / header

number of digital inputs	11
Digital inputs / note	of which: 5 DI and 3 F-DI (= 6 DI)
DC input voltage	
• rated value	24 V
• for signal "1"	15 ... 30 V
• for signal "0"	-3 ... +5 V
Electrical isolation	Yes
Current consumption for "1" signal level, typ.	3.5 mA
Input delay time for	
• signal "0" → "1", typ.	50 µs
• signal "1" → "0", typ.	150 µs

Digital inputs/outputs / header

Number of digital I/Os	8
Parameterization possibility of the digital I/Os	can be parameterized - as DI - as DO - as probe input (max. 8) - as cam output (max. 8)

If used as an input / header

DC input voltage	
• rated value	24 V
• for signal "1"	15 ... 30 V
• for signal "0"	-3 ... +5 V
Electrical isolation	No
Current consumption for "1" signal level, typ.	3.5 mA
Input delay time for	
• signal "0" → "1", typ.	5 µs
• signal "1" → "0", typ.	50 µs
Measuring input / reproducibility	5 µs
• note	typical value
Measuring input / resolution	1 µs

If used as an output / header

Load voltage	
• rated value	24 V
• minimum	20.4 V
• maximum	28.8 V
Electrical isolation	No
Current carrying capacity for each output, max.	500 mA
Leakage current, max.	2 mA
Output delay for	
• signal "0" → "1", typ.	150 µs
• signal "0" → "1", max.	400 µs
• signal "1" → "0", typ.	75 µs
• signal "1" → "0", max.	100 µs
— note	Data for Vcc = 24 V; load 48 Ohm; "1" = 90 % VOut, "0" = 10 % VOut

Cam output	
<ul style="list-style-type: none"> • reproducibility <ul style="list-style-type: none"> — note • resolution <ul style="list-style-type: none"> — note 	125 μ s typical value 125 μ s typical value
Switching frequency of the outputs for	
<ul style="list-style-type: none"> • resistive load, max. • inductive load, max. • lamp load, max. 	100 Hz 0.5 Hz 10 Hz
Short-circuit protection	Yes

Digital outputs / header

Number of digital outputs	1
Parameterization possibility of the digital outputs	can be parameterized as F-DO or DO
Load voltage	
<ul style="list-style-type: none"> • rated value • minimum • maximum 	24 V 20.4 V 28.8 V
Electrical isolation	Yes
Current carrying capacity for each output, max.	500 mA
Leakage current, max.	2 mA
Output delay for	
<ul style="list-style-type: none"> • signal "0" \rightarrow "1", typ. • signal "0" \rightarrow "1", max. • signal "1" \rightarrow "0", typ. • signal "1" \rightarrow "0", max. — note 	150 μ s 400 μ s 75 μ s 100 μ s Data for $V_{cc} = 24$ V; load 48 Ohm; "1" = 90 % V_{Out} , "0" = 10 % V_{Out}
Short-circuit protection	Yes

Analog inputs / header

number of analog inputs	1
-------------------------	---

If used as an voltage input / header

Input voltage	-10 ... +10 V
Resolution	12 bit
<ul style="list-style-type: none"> • note 	+sign
Input resistance (Ri)	100 k Ω

If used as an current input / header

Input current	-20 ... +20 mA
Resolution	11 bit
<ul style="list-style-type: none"> • Note 	+ sign
Input resistance (Ri)	250 Ω

Onboard encoder interface / header

Encoder interface	optional incremental encoder TTL, incremental encoder HTL or absolute encoder SSI without incremental signals TTL/HTL
Encoder supply for	
<ul style="list-style-type: none"> • 24 VDC • 5 VDC 	0.35 A 0.35 A
Limiting frequency, max.	500 kHz
SSI baud rate	100 ... 1 000
Resolution of absolute position SSI	30 bit
Cable length for	
<ul style="list-style-type: none"> • TTL incremental encoder, max. • HTL incremental encoder for <ul style="list-style-type: none"> — unipolar signals, max. — bipolar signals, max. — note • SSI absolute encoder, max. — note 	100 m 100 m 300 m TTL only bipolar signals; for bipolar signals, the signal lines must be twisted in pairs and shielded 100 m max. cable length depends on the baud rate

Additional technical data

design of the sensor / to detect the ambient temperature / connectable	KTY84-130, PT1000 or PTC
Back-up of non-volatile data	
<ul style="list-style-type: none"> • of retentive data • of real-time clock, min. 	unlimited buffer duration 5 d

- note

Approvals

- USA
- Canada
- Australia
- Korea
- Russia, Belarus and Kazakhstan

Data buffering is maintenance-free

cULus
cULus
RCM (formerly C-Tick)
KCC
EAC

