

product type designation

PROFIBUS connector

SIPLUS NET PB Connector based on 6GK1500-0EA02 with conformal coating, -25...+60 °C,



transfer rate

transfer rate / with PROFIBUS	9.6 kbit/s ... 12 Mbit/s
-------------------------------	--------------------------

ambient conditions

ambient temperature	70 ... -40 °C
<ul style="list-style-type: none"> in horizontal mounting position / during operation during storage and transport 	70 ... -40 °C
relative humidity	100 %; RH incl. condensation / frost (no commissioning in bedewed state), horizontal installation
<ul style="list-style-type: none"> with condensation / according to IEC 60068-2-38 / maximum 	
type of coating	Yes; Class PC2 protective coating acc. to EN 50155:2017
<ul style="list-style-type: none"> for electronic devices in railway applications according to EN 50155 	

standards, specifications, approvals

reference code	X
<ul style="list-style-type: none"> according to IEC 81346-2 	

further information / internet-Links

Internet-Link	
<ul style="list-style-type: none"> to web page: selection aid TIA Selection Tool to website: Industrial communication to website: Industry Mall to website: Information and Download Center to website: Selection guide for cables and connectors to website: Image database to website: CAx-Download-Manager to website: Industry Online Support 	http://www.siemens.com/snst http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter https://sie.ag/2QdlxcP http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com

last modified:

10/15/2022