



Figure similar

SITOP MODULAR/3AC/24VDC/20A/CO

SITOP modular plus 20 A Stabilized power supply input: 3 AC 400-500 V
output: 24 V DC/20 A Option for with protective varnish

Input	
type of the power supply network	3-phase AC
supply voltage at AC	
<ul style="list-style-type: none"> • minimum rated value • maximum rated value • initial value • full-scale value 	400 V 500 V 320 V; Starting from $V_{in} > 340$ V 550 V
design of input wide range input	Yes
overvoltage overload capability	$2.3 \times V_{in}$ rated, 1.3 ms
operating condition of the mains buffering	at $V_{in} = 400$ V
buffering time for rated value of the output current in the event of power failure minimum	6 ms
operating condition of the mains buffering	at $V_{in} = 400$ V
line frequency	
<ul style="list-style-type: none"> • 1 rated value • 2 rated value 	50 Hz 60 Hz
line frequency	47 ... 63 Hz
input current	
<ul style="list-style-type: none"> • at rated input voltage 400 V • at rated input voltage 500 V 	1.1 A 0.9 A
current limitation of inrush current at 25 °C maximum	35 A
I ² t value maximum	0.7 A ² ·s
fuse protection type	none
<ul style="list-style-type: none"> • in the feeder 	Required: 3-pole connected miniature circuit breaker 6 ... 16 A characteristic C or circuit breaker 3RV2011-1DA10 (setting 3 A) or 3RV2711-1DD10 (UL 489)
Output	
voltage curve at output	Controlled, isolated DC voltage
output voltage at DC rated value	24 V
output voltage	
<ul style="list-style-type: none"> • at output 1 at DC rated value 	24 V
relative overall tolerance of the voltage	3 %
relative control precision of the output voltage	
<ul style="list-style-type: none"> • on slow fluctuation of input voltage • on slow fluctuation of ohm loading 	0.1 % 0.2 %
residual ripple	
<ul style="list-style-type: none"> • maximum 	100 mV
voltage peak	
<ul style="list-style-type: none"> • maximum 	200 mV
adjustable output voltage	24 ... 28.8 V
product function output voltage adjustable	Yes

type of output voltage setting	via potentiometer; max. 480 W
display version for normal operation	Green LED for 24 V OK
type of signal at output	via signaling module (6EP1961-3BA10)
behavior of the output voltage when switching on	No overshoot of Vout (soft start)
response delay maximum	2.5 s
voltage increase time of the output voltage	
• maximum	500 ms
output current	
• rated value	20 A
• rated range	0 ... 20 A; +60 ... +70 °C: Derating 2%/K
supplied active power typical	480 W
short-term overload current	
• at short-circuit during operation typical	60 A
duration of overloading capability for excess current	
• at short-circuit during operation	25 ms
constant overload current	
• on short-circuiting during the start-up typical	23 A
product feature	
• bridging of equipment	Yes; switchable characteristic
number of parallel-switched equipment resources for increasing the power	2

Efficiency

efficiency in percent	90 %
power loss [W]	
• at rated output voltage for rated value of the output current typical	53 W

Closed-loop control

relative control precision of the output voltage with rapid fluctuation of the input voltage by +/- 15% typical	1 %
relative control precision of the output voltage load step of resistive load 50/100/50 % typical	2 %
setting time	
• load step 50 to 100% typical	4 ms
• load step 100 to 50% typical	4 ms
setting time	
• maximum	10 ms

Protection and monitoring

design of the overvoltage protection	< 35 V
• typical	23 A
property of the output short-circuit proof	Yes
design of short-circuit protection	Alternatively, constant current characteristic approx. 23 A or latching shutdown
enduring short circuit current RMS value	
• typical	23 A
display version for overload and short circuit	LED yellow for "overload", LED red for "latching shutdown"

Safety

galvanic isolation between input and output	Yes
galvanic isolation	Safety extra-low output voltage Uout acc. to EN 60950-1 and EN 50178
operating resource protection class	Class I
leakage current	
• maximum	3.5 mA
protection class IP	IP20

Approvals

certificate of suitability	
• CE marking	Yes
• UL approval	Yes; UL-Listed (UL 508), File E197259; CSA (CSA C22.2 No. 14, CSA C22.2 No. 107.1)
• CSA approval	Yes; UL-Listed (UL 508), File E197259, CSA (CSA C22.2 No. 14, CSA C22.2 No. 107.1)
• cCSAus, Class 1, Division 2	No
• ATEX	No
certificate of suitability	
• IECEx	No
• NEC Class 2	No

<ul style="list-style-type: none"> • ULhazloc approval 	No
<ul style="list-style-type: none"> • FM registration 	No
type of certification CB-certificate	No
certificate of suitability	
<ul style="list-style-type: none"> • EAC approval 	Yes
certificate of suitability shipbuilding approval	No
shipbuilding approval	-
Marine classification association	
<ul style="list-style-type: none"> • American Bureau of Shipping Europe Ltd. (ABS) 	No
<ul style="list-style-type: none"> • French marine classification society (BV) 	No
<ul style="list-style-type: none"> • DNV GL 	No
<ul style="list-style-type: none"> • Lloyds Register of Shipping (LRS) 	No
<ul style="list-style-type: none"> • Nippon Kaiji Kyokai (NK) 	No

EMC

standard	
<ul style="list-style-type: none"> • for emitted interference 	EN 55022 Class B
<ul style="list-style-type: none"> • for mains harmonics limitation 	EN 61000-3-2
<ul style="list-style-type: none"> • for interference immunity 	EN 61000-6-2

environmental conditions

ambient temperature	
<ul style="list-style-type: none"> • during operation 	0 ... 70 °C; with natural convection
<ul style="list-style-type: none"> • during transport 	-40 ... +85 °C
<ul style="list-style-type: none"> • during storage 	-40 ... +85 °C
environmental category according to IEC 60721	Climate class 3K3, 5 ... 95% no condensation

Mechanics

type of electrical connection	screw-type terminals
<ul style="list-style-type: none"> • at input 	L1, L2, L3, PE: 1 screw terminal each for 0.2 ... 4 mm ² single-core/finely stranded
<ul style="list-style-type: none"> • at output 	+, -: 2 screw terminals each for 0.33 ... 4 mm ²
<ul style="list-style-type: none"> • for auxiliary contacts 	-
width of the enclosure	160 mm
height of the enclosure	125 mm
depth of the enclosure	125 mm
required spacing	
<ul style="list-style-type: none"> • top 	50 mm
<ul style="list-style-type: none"> • bottom 	50 mm
<ul style="list-style-type: none"> • left 	0 mm
<ul style="list-style-type: none"> • right 	0 mm
net weight	2 kg
product feature of the enclosure housing can be lined up	Yes
fastening method	Snaps onto DIN rail EN 60715 35x7.5/15
electrical accessories	Buffer module, signaling module
MTBF at 40 °C	711 213 h
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

