



SITOP SEL1400/8X2-10A

SITOP SEL1400 10 A selectivity module 8-channel with limiting characteristic input: 24 V DC/60 A output: 24 V DC/8x 10 A threshold adjustable 2-10 A with monitoring interface \*Ex approval no longer available\*

Input	
type of the power supply network	Controlled DC voltage
supply voltage at DC rated value	24 V
input voltage at DC	20.4 ... 30 V
overvoltage overload capability	35 V
input current at rated input voltage 24 V rated value	60 A
Output	
voltage curve at output	controlled DC voltage
formula for output voltage	Vin - approx. 0.2 V
relative overall tolerance of the voltage note	In accordance with the supplying input voltage
number of outputs	8
output current up to 60 °C per output rated value	10 A
adjustable current response value current of the current-dependent overload release	2 ... 10 A
type of response value setting	via potentiometer
product feature parallel switching of outputs	Yes
type of outputs connection	Connection of all outputs after ramp-up of the supply voltage > 20 V; delay time of 25 ms, 200 ms, 500 ms or "load-optimized" can be set via DIP switch for sequential connection
Efficiency	
efficiency in percent	98 %
power loss [W] at rated output voltage for rated value of the output current typical	18 W
Switch-off characteristic per output	
switching characteristic	<ul style="list-style-type: none"> <li>• of the excess current</li> <li>• of the current limitation</li> <li>• of the immediate switch-off</li> </ul>
design of the reset device/resetting mechanism	Iout = 1.0 ... 1.5 x set value, switch-off after approx. 5 s Iout = 1.5 x set value, switch-off after typ. 100 ms Iout > set value and Vin < 20 V, switch-off after approx. 0.5 ms via sensor per output Non-electrically isolated 24 V input (signal level "high" at > 15 V)
remote reset function	
Protection and monitoring	
fuse protection type at input	15 A per output (not accessible)
display version for normal operation	Three-color LED per output: green LED for "Output switched through"; yellow LED for "Output switched off manually"; red LED for "Output switched off due to overcurrent"
design of the switching contact for signaling function	Floating common signal contact or status signal output (pulse/pause signal that can be evaluated via SIMATIC function block)
Safety	
galvanic isolation between input and output at switch-off	No
standard for safety	according to EN 60950-1 and EN 50178
operating resource protection class	Class III
protection class IP	IP20

Approvals	
certificate of suitability	
• CE marking	Yes
• UL approval	Yes; UL-Recognized (UL 2367) File E328600; cULus-Listed (UL 508, CSA C22.2 No. 107.1) File E197259
• CSA approval	Yes; CSA 22.2 60950-1
• ATEX	No
certificate of suitability	
• IECEx	No
type of certification CB-certificate	Yes
certificate of suitability	
• EAC approval	Yes
EMC	
standard	
• for emitted interference	EN 61000-6-3
• for interference immunity	EN 61000-6-2
environmental conditions	
ambient temperature	
• during operation	-25 ... +70 °C; with natural convection
• during transport	-40 ... +85 °C
• during storage	-40 ... +85 °C
environmental category according to IEC 60721	Climate class 3K3, 5 ... 95% no condensation
Mechanics	
type of electrical connection	Push-in
• at input	24V1, 24V2: push-in for 0.5 ... 16 mm <sup>2</sup> ; 0V1, 0V2: push-in for 0.5 ... 4 mm <sup>2</sup>
• at output	1 - 8: push-in for 0.5 ... 4 mm <sup>2</sup>
• for signaling contact	13, 14: push-in for 0.2 ... 1.5 mm <sup>2</sup>
• for auxiliary contacts	RST: push-in for 0.2 ... 1.5 mm <sup>2</sup>
width of the enclosure	45 mm
height of the enclosure	135 mm
depth of the enclosure	125 mm
installation width	45 mm
mounting height	225 mm
required spacing	
• top	45 mm
• bottom	45 mm
• left	0 mm
• right	0 mm
net weight	0.3 kg
fastening method	Snaps onto DIN rail EN 60715 35x7.5/15
MTBF at 40 °C	363 000 h
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

