

Ba15d continuous light module; red

Part no.	SL4-L-R
Catalog No.	171333
Alternate Catalog No.	SL4-L-R
EL-Nummer	4137568
(Norway)	

Delivery program

Product range			SL signal towers
Basic function			Continuous light module
Degree of Protection			IP66
Rated operational voltage	U _e	V	< 250 V AC/DC
Description			without light elements
Type of light			Continuous light
Light elements			Filament lamp max. 4 W
Colour			Red
Connection to SmartWire-DT			no

Technical data

General			
Standards			IEC/EN 60947-5-1
Climatic proofing			Damp heat, cyclic, to IEC 60068-2-30
Mounting position			As required
Mechanical shock resistance	g		> 15 according to IEC 60068-2-27 Shock duration 11 ms Sinusoidal
IEC degree of protection			IP66 IEC/EN 60529
Protection type UL			Type 4, 4X, 13
Material			Enclosure: Polycarbonate (PC), black Cap: Polycarbonate (PC)
Cap colour			Red
Ambient temperature	°C		-30 - +60
Number of signal elements			Max. 5 with standard base Max. 10 with base for mounting on both sides
Weight	g		45

Contacts

Rated impulse withstand voltage	U _{imp}	V AC	4000
Rated insulation voltage	U _i	V	250
Overvoltage category/pollution degree			III/3

modules

Type of light			Continuous light
Light elements			Filament lamp max. 4 W
Mounting			Ba15d
Leakage current	A		< 0.003
lifespan	h		> 3000
Transmission angle			360°
Current-/power consumption			Max. 4 W with the specified voltages
Power consumption			up to 250 V AC/DC
Voltage range			

Design verification as per IEC/EN 61439

Technical data for design verification

Operating ambient temperature min.	°C	-30
Operating ambient temperature max.	°C	60

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Optical module for signal tower (EC000232)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Optical module for signal tower (ecl@ss10.0.1-27-37-12-20 [AKF038014])

Function		Continuous light
Colour		Red
Outer diameter	mm	43
Operating voltage at AC 50 Hz	V	24 - 250
Operating voltage at AC 60 Hz	V	24 - 250
Operating voltage at DC	V	24 - 250
Voltage type		AC/DC
Lamp type		None
Colour housing		Black
Degree of protection (IP)		IP66
Degree of protection (NEMA)		4X