

product type designation

IWLAN terminating resistor TI795-1R RSMA Male

R-SMA male termination Impedance TI795-1R 2.4 and 5 GHz, IP65, 0...6 GHz; 1 pack=3 units.



electrical data

number of electrical connections	1
type of electrical connection	R-SMA male
transmission frequency	0 ... 6 GHz
impedance	50 Ω
return loss / minimum	25 dB

ambient conditions

ambient temperature	
<ul style="list-style-type: none"> during operation 	-40 ... +70 °C
<ul style="list-style-type: none"> during storage 	-40 ... +70 °C
<ul style="list-style-type: none"> during transport 	-40 ... +70 °C
protection class IP	IP65

design, dimensions and weights

diameter	9 mm
length	15 mm
net weight	5 g

standards, specifications, approvals

<ul style="list-style-type: none"> certificate of suitability / RoHS conformity 	Yes
--	-----

further information / internet links

internet link	
<ul style="list-style-type: none"> to website: Selection guide for cables and connectors to web page: selection aid TIA Selection Tool to website: Industrial communication to the website: IWLAN to website: Image database to website: CAx-Download-Manager to website: Industry Online Support 	https://sie.ag/2QdlxcP http://www.siemens.com/snst http://www.siemens.com/simatic-net http://www.siemens.com/iwlan http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com

last modified:

9/12/2023 