

## RC suppressor circuit, 110-240VAC, for DILA, DILM7-12

**Part no.** DILM12-XSPR240  
**Catalog No.** 281200  
**Alternate Catalog No.** XTCEXRSBB  
**EL-Nummer (Norway)** 4131888

Similar to illustration

## Delivery program

|               |                |   |                                                                                                                                                          |
|---------------|----------------|---|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product range |                |   | Accessories                                                                                                                                              |
| Accessories   |                |   | Suppressor circuit                                                                                                                                       |
| Voltage       | U <sub>s</sub> | V | 110 - 240 AC                                                                                                                                             |
| For use with  |                |   | DILM7 - DILM15<br>DILMP20<br>DILA                                                                                                                        |
| Instructions  |                |   | For AC operation contactors 50 - 60 Hz.<br>With DC operated contactors and with DILM115 and DILM150 the suppressor is integrated.<br>Note drop-out delay |

## Design verification as per IEC/EN 61439

|                                                                                                                        |                   |    |                                                                                                                                  |
|------------------------------------------------------------------------------------------------------------------------|-------------------|----|----------------------------------------------------------------------------------------------------------------------------------|
| Technical data for design verification                                                                                 |                   |    |                                                                                                                                  |
| Rated operational current for specified heat dissipation                                                               | I <sub>n</sub>    | A  | 0                                                                                                                                |
| Heat dissipation per pole, current-dependent                                                                           | P <sub>vid</sub>  | W  | 0                                                                                                                                |
| Equipment heat dissipation, current-dependent                                                                          | P <sub>vid</sub>  | W  | 0                                                                                                                                |
| Static heat dissipation, non-current-dependent                                                                         | P <sub>vs</sub>   | W  | 0                                                                                                                                |
| Heat dissipation capacity                                                                                              | P <sub>diss</sub> | W  | 0                                                                                                                                |
| Operating ambient temperature min.                                                                                     |                   | °C | -25                                                                                                                              |
| Operating ambient temperature max.                                                                                     |                   | °C | 60                                                                                                                               |
| IEC/EN 61439 design verification                                                                                       |                   |    |                                                                                                                                  |
| 10.2 Strength of materials and parts                                                                                   |                   |    |                                                                                                                                  |
| 10.2.2 Corrosion resistance                                                                                            |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.3.1 Verification of thermal stability of enclosures                                                               |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat                                             |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.4 Resistance to ultra-violet (UV) radiation                                                                       |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.2.5 Lifting                                                                                                         |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.2.6 Mechanical impact                                                                                               |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.2.7 Inscriptions                                                                                                    |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.3 Degree of protection of ASSEMBLIES                                                                                |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.4 Clearances and creepage distances                                                                                 |                   |    | Meets the product standard's requirements.                                                                                       |
| 10.5 Protection against electric shock                                                                                 |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.6 Incorporation of switching devices and components                                                                 |                   |    | Does not apply, since the entire switchgear needs to be evaluated.                                                               |
| 10.7 Internal electrical circuits and connections                                                                      |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.8 Connections for external conductors                                                                               |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.9 Insulation properties                                                                                             |                   |    |                                                                                                                                  |
| 10.9.2 Power-frequency electric strength                                                                               |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.9.3 Impulse withstand voltage                                                                                       |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.9.4 Testing of enclosures made of insulating material                                                               |                   |    | Is the panel builder's responsibility.                                                                                           |
| 10.10 Temperature rise                                                                                                 |                   |    | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating                                                                                             |                   |    | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |

|                                     |  |  |                                                                                                          |
|-------------------------------------|--|--|----------------------------------------------------------------------------------------------------------|
| 10.12 Electromagnetic compatibility |  |  | Is the panel builder's responsibility. The specifications for the switchgear must be observed.           |
| 10.13 Mechanical function           |  |  | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

## Technical data ETIM 8.0

|                                                                                                                                                                             |  |   |            |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|---|------------|
| Low-voltage industrial components (EG000017) / Surge protection module (EC000683)                                                                                           |  |   |            |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Overvoltage limiter (ecl@ss10.0.1-27-37-10-13 [AKF022013]) |  |   |            |
| Function                                                                                                                                                                    |  |   | RC-element |
| Rated control supply voltage Us at AC 50HZ                                                                                                                                  |  | V | 110 - 240  |
| Rated control supply voltage Us at AC 60HZ                                                                                                                                  |  | V | 110 - 240  |
| Rated control supply voltage Us at DC                                                                                                                                       |  | V | 0 - 0      |
| Voltage type for actuating                                                                                                                                                  |  |   | AC         |
| With LED indication                                                                                                                                                         |  |   | No         |