

Control transformer, 0.315 kVA, Rated input voltage 208 – 600 V, Rated output voltage 2 x 115 V



Part no. UTI0,315-115  
 Catalog No. 206925  
 Alternate Catalog No. UTIP32-AI

### Delivery program

|  |  |     |   |
|--|--|-----|---|
| Product range  |  |     | Single-phase UTI multi-winding transformers |
| Rated input voltage  |  | V   | 208 – 600                                   |
| Rated output voltage   |  | V   | 2 x 115                                     |
| Rated power  |  | kVA | 0.315                                       |
| Cu factor 1,10   |  |     |   |
| <b>Notes</b>   |  |     |   |
| The transformers UTI are suitable for use in control circuits to IEC/EN 60204 or VDE 0113. |  |     |   |
| Transformer-protective circuit-breaker →#088907  |  |     |   |

### Technical data

#### General

|                     |  |  |   |
|---------------------|--|--|---|
| Standards           |  |  |   |
| Built and tested to |  |  | (universal) control, isolating and safety transformers to VDE 0550<br>IEC/EN 61558-2-2/2-4/2-6<br>VDE 0570 Part 2-2/2-6 (safety transformer)<br>VDE 0570 Part 2-4 (isolating transformer) |
| Suitable for use to |  |  | IEC/EN 60204-1, ÖVE-EN 13<br>VDE 0113, VDE 0100 Part 410  |
| Ambient temperature |  |  | -25 - 40  |

#### Characteristics

|                          |  |      |         |
|--------------------------|--|------|---------|
| Terminations             |  |      | ●       |
| Insulation class         |  |      | B       |
| Rated frequency          |  | Hz   | 50 - 60 |
| Primary tapping          |  |      | ± 20 %  |
| Degree of Protection     |  |      | IP00    |
| Separate windings        |  |      | ●       |
| Fully vacuum-impregnated |  |      | ●       |
| Reinforced insulation    |  |      | ●       |
| Rated duty factor        |  | % DF | 100     |

#### Electrical characteristics

|                      |  |    |   |
|----------------------|--|----|---|
| Note                 |  |    | The following applies for the no-load loss, short-circuit loss (copper losses), short-circuit voltage and efficiency values: all details relate to a temperature of 20 °C |
| Total weight         |  | kg | 4.3   |
| No-load losses       |  | W  | 15  |
| Short-circuit losses |  | W  | 23  |
| Shortcircuit voltage |  | %  | 5   |
| Efficiency           |  |    | 0.892   |

### Design verification as per IEC/EN 61439

|  |            |    |     |
|--|------------|----|-----|
| Technical data for design verification                   |            |    |     |
| Rated operational current for specified heat dissipation | $I_n$      | A  | 0   |
| Heat dissipation per pole, current-dependent             | $P_{vid}$  | W  | 0   |
| Equipment heat dissipation, current-dependent            | $P_{vid}$  | W  | 0   |
| Static heat dissipation, non-current-dependent           | $P_{vs}$   | W  | 38  |
| Heat dissipation capacity                                | $P_{diss}$ | W  | 0   |
| Operating ambient temperature min.                       |            | °C | -25 |

|  |  |    |  |
|--|--|----|--|
| Operating ambient temperature max.   |  | °C | 40   |
| IEC/EN 61439 design verification   |  |    |  |
| 10.2 Strength of materials and parts   |  |    |  |
| 10.2.2 Corrosion resistance  |  |    | Meets the product standard's requirements.   |
| 10.2.3.1 Verification of thermal stability of enclosures   |  |    | Meets the product standard's requirements.   |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat   |  |    | Meets the product standard's requirements.   |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects |  |    | Meets the product standard's requirements.   |
| 10.2.4 Resistance to ultra-violet (UV) radiation   |  |    | Meets the product standard's requirements.   |
| 10.2.5 Lifting   |  |    | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.6 Mechanical impact   |  |    | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.2.7 Inscriptions  |  |    | Meets the product standard's requirements.   |
| 10.3 Degree of protection of ASSEMBLIES  |  |    | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.4 Clearances and creepage distances   |  |    | Meets the product standard's requirements.   |
| 10.5 Protection against electric shock   |  |    | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.6 Incorporation of switching devices and components   |  |    | Does not apply, since the entire switchgear needs to be evaluated.   |
| 10.7 Internal electrical circuits and connections  |  |    | Is the panel builder's responsibility.   |
| 10.8 Connections for external conductors   |  |    | Is the panel builder's responsibility.   |
| 10.9 Insulation properties   |  |    |  |
| 10.9.2 Power-frequency electric strength   |  |    | Is the panel builder's responsibility.   |
| 10.9.3 Impulse withstand voltage   |  |    | Is the panel builder's responsibility.   |
| 10.9.4 Testing of enclosures made of insulating material   |  |    | Is the panel builder's responsibility.   |
| 10.10 Temperature rise   |  |    | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating   |  |    | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.12 Electromagnetic compatibility  |  |    | Is the panel builder's responsibility. The specifications for the switchgear must be observed.                                   |
| 10.13 Mechanical function  |  |    | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.                         |

## Technical data ETIM 8.0

|   |   |  |           |
|---|---|--|-----------|
| Low-voltage industrial components (EG000017) / One-phase control transformer (EC002486)   |   |  |           |
| Electric engineering, automation, process control engineering / Transformer, converter, coil / Control transformer / One-phase control transformer (ec @ss10.0.1-27-03-13-02 [AAB620015]) |   |  |           |
| Built as safety transformer   |   |  | Yes       |
| Built as isolating transformer  |   |  | Yes       |
| Built as energy saving transformer  |   |  | No        |
| Primary voltage 1   | V |  | 208 - 600 |
| Primary voltage 2   | V |  | 0 - 0     |
| Primary voltage 3   | V |  | 0 - 0     |
| Primary voltage 4   | V |  | 0 - 0     |
| Primary voltage 5   | V |  | 0 - 0     |
| Primary voltage 6   | V |  | 0 - 0     |
| Primary voltage 7   | V |  | 0 - 0     |
| Primary voltage 8   | V |  | 0 - 0     |
| Primary voltage 9   | V |  | 0 - 0     |
| Primary voltage 10  | V |  | 0 - 0     |
| Secondary voltage 1   | V |  | 115 - 115 |
| Secondary voltage 2   | V |  | 115 - 115 |
| Secondary voltage 3   | V |  | 0 - 0     |
| Secondary voltage 4   | V |  | 0 - 0     |
| Secondary voltage 5   | V |  | 0 - 0     |
| Secondary voltage 6   | V |  | 0 - 0     |
| Secondary voltage 7   | V |  | 0 - 0     |
| Secondary voltage 8   | V |  | 0 - 0     |
| Secondary voltage 9   | V |  | 0 - 0     |
| Secondary voltage 10  | V |  | 0 - 0     |

|   |    |        |
|---|----|--------|
| Rated apparent power                            | VA | 315    |
| Type of insulation material according to IEC 85 |    | B      |
| Short-circuit-proof                             |    | No     |
| Relative short circuit voltage                  | %  | 5      |
| Width   | mm | 121    |
| Height  | mm | 124    |
| Depth   | mm | 88     |
| Degree of protection (IP)                       |    | IP00   |
| Ring core                                       |    | No     |
| Suitable for mounting on PCB                    |    | No     |
| Modular version                                 |    | No     |
| Conductor material                              |    | Copper |