

Release relay, 250VAC, 1 N/C, 3-8A, 1HP

Part no. **Z-LAR8-0**
 Catalog No. **248256**



Technical data ETIM 8.0

Devices for distribution board-/surface mounting (EG000062) / Load shedding relay for distribution board (EC001655)

Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Load shedding relay for distribution board (ecl@ss10.0.1-27-14-23-32 [ACN383011])

| | | |
|---|-----------------|----------|
| Rated voltage | V | 250 |
| Rated current I_{u} | A | 3 - 8 |
| Just-operate current | A | 3 - 8 |
| Max. time-delayed switch-off | ms | 0 |
| Max. continuous current | A | 10 |
| Number of contacts as normally open contact | | 0 |
| Number of contacts as normally closed contact | | 1 |
| Number of contacts as change-over contact | | 0 |
| Rated current (control contacts) | A | 1 |
| Max. switching voltage (control contacts) | V | 250 |
| Max. switching power (control contacts) | VA | 7.7 |
| Electrical lifespan (control contacts) | c (contacts) | 100000 |
| Mechanical lifetime (control contacts) | c (contacts) | 0 |
| Max. electrical switching cycles | c/h | 3600 |
| Voltage type | | AC |
| Mounting method | | DIN rail |
| Width in number of modular spacings | | 1 |
| Built-in depth | mm | 60 |
| Degree of protection (IP) | | IP20 |