

Shunt release, up to 125A, 12-60V, 1.5HP



Powering Business Worldwide™

Part no.	Z-LHASA/24
Catalog No.	248441
Alternate Catalog No.	Z-LHASA/24
EL-Nummer	1609567
(Norway)	

Similar to illustration

Delivery program

Basic function	Accessories for miniature circuit-breaker
Basic function accessories	Shunt release
Application	Switchgear for industrial and advanced commercial applications
Product range	Accessory
Side mounting	for fitting on left to: AZ

Technical data

Electrical

Rated operational voltage	U _e	V AC	8
Voltage range		V AC	12-60
Voltage range		V DC	12-60
Rated impulse withstand voltage	U _{imp}	kV	2

Mechanical

Mounting width	mm	27 (1.5 MU)
Degree of protection		IP40
Integrated		
Terminals		Lift terminals
Tightening torque of terminal screws	Nm	4

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.	°C	-5	
Operating ambient temperature max.	°C	40	

Technical data ETIM 8.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)		
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ec1@ss10.0.1-27-14-35-02 [AKE327013])		
Device fitting		Miniature circuit breaker (MCB)
Additional equipment		Shunt release (for power circuit breaker)
Installed at the factory		No
Width in number of modular spacings		1.5
Number of contacts as normally open contact		1
Number of contacts as normally closed contact		1
Number of contacts as change-over contact		0
Number of fault-signal switches		0
Rated switch current	A	18
Rated voltage	V	24
Voltage type for actuating		AC
With auto test for earth leakage function		No
Suitable for max. number of poles main contact unit (total)		1
Suitable for max. current main contact unit	A	14

