

## Control switchp13 S16A, 230 V, 20kA

Part no. **Z-S/3S**  
Catalog No. **248334**

EL-Nummer **4355526**  
(Norway)

## Design verification as per IEC/EN 61439

Technical data for design verification	I <sub>n</sub>	A	20
Rated operational current for specified heat dissipation			

## Technical data ETIM 7.0

Devices for distribution board-/surface mounting (EG000062) / Main switch for distribution board (EC001545)			
Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Main switch for distribution board (ecl@ss10.0.1-27-14-23-01 [AFZ813014])			
Switching function		Control switch	
Number of contacts as normally open contact		3	
Number of contacts as normally closed contact		0	
Number of contacts as change-over contact		0	
Number of poles		3	
Rated current	A	20	
Rated voltage	V	240	
Min. rated voltage	V	0	
Rated switching capacity	kA	0.025	
Short-circuit breaking capacity (Icw)	kA	10	
Voltage type		AC	
With signal lamp		No	
Colour calotte		Other	
Lamp type		Other	
Lamp socket		Other	
Max. lamp power	W	0	
Width in number of modular spacings		1	
Built-in depth	mm	80	
Degree of protection (IP)		IP40	
Imprint/indication		EV000154	