

Fuse-link with blink application, D01, 2A, 24 V, gL/gG, set consists of 3 pcs.



Part no. Z-SLS/B-24-2A
Catalog No. 268995

Similar to illustration

Delivery program

Product range		Fuse material	
Basic function		Accessories	
Basic function		Fuse sets	
For use with		Z-SLS/NEOZ Z-SLK/NEOZ Z-SLS/CEK	
		With flashing function Snap-fit on DIN rail 1 set consists of: 3 fuse-links, 3 current codings, 1 plastic box in the colour of the indicator	
Rated operating voltage		24 - 60 V AC/DC	
Rated uninterrupted current	I _u	A	2

Technical data

Electrical

Rated operational voltage	U _e	V	
Rated operating voltage	U _e	V AC	24 - 60
		V DC	24 - 60
Utilization category			gG (gL)
Test voltage		kV	5

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	55

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / D0-system fuse link (EC001642)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Neozed fuse link (ecl@ss10.0.1-27-14-21-19 [ACN353011])			
Construction size		D01	
Rated current	A	2	
Rated voltage	V	24	
Colour code		Pink	
Utilization category		gL/gG (cable protection/equipment protection)	