

Fuse-link with blink application, D01, 4A, 400 V, gL/gG, set consists of 3 pcs.



Part no. **Z-SLS/B-4A**  
 Catalog No. **268985**

Similar to illustration

## Delivery program

Product range			Fuse material
Basic function			Accessories
Basic function			Fuse sets
For use with			Z-SLS/NEOZ Z-SLK/NEOZ Z-SLS/CEK
			With flashing function Snap-fit on DIN rail 1 set consists of: 3 fuse-links, 3 current codings, 1 plastic box in the colour of the indicator
Rated operating voltage			50 - 400 V AC, 50 - 250 V DC
Rated uninterrupted current	I <sub>u</sub>	A	4

## Technical data

### Electrical

Rated operational voltage	U <sub>e</sub>	V	
Rated operating voltage	U <sub>e</sub>	V AC	50 - 400
		V DC	50 - 250
Utilization category			gG (gL)
Test voltage		kV	5

## Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	I <sub>n</sub>	A	4
Heat dissipation per pole, current-dependent	P <sub>vid</sub>	W	0
Equipment heat dissipation, current-dependent	P <sub>vid</sub>	W	1.2
Static heat dissipation, non-current-dependent	P <sub>vs</sub>	W	0
Heat dissipation capacity	P <sub>diss</sub>	W	0
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	55
			0

## Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / D0-system fuse link (EC001642)

Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Neozed fuse link (ecl@ss10.0.1-27-14-21-19 [ACN353011])

Construction size		D01
Rated current	A	4
Rated voltage	V	400
Colour code		Brown
Utilization category		gL/gG (cable protection/equipment protection)