

Terminal, spring-loaded terminal, 4 clamping points, PE/PEN terminal, 4 mm², green-yellow



| Model | |
|---|--------------------------|
| product brand name | ALPHA |
| product designation | PE through-type terminal |
| General technical data | |
| insulation material | thermoplastic |
| terminal contact spacing | 6.2 mm |
| Protection class | |
| combustibility class according to UL 94 | V0 |
| Appearance | |
| color | miscellaneous |
| Product details | |
| product component required end cover plate | Yes |
| Number | |
| number of terminal levels | 1 |
| number of terminal points per terminal level | 4 |
| Connections | |
| stripped length | 9 mm |
| connectable conductor cross-section solid | |
| • minimum | 0.08 mm ² |
| • maximum | 6 mm ² |
| connectable conductor cross-section stranded | |
| • minimum | 4 mm ² |
| • maximum | 0.08 mm ² |
| connectable conductor cross-section finely stranded | |
| • with core end processing minimum | 0.14 mm ² |
| • with core end processing maximum | 4 mm ² |
| • without core end processing minimum | 0.08 mm ² |
| • without core end processing maximum | 4 mm ² |
| type of connection 1 | spring-loaded terminal |
| type of connection 2 | spring-loaded terminal |
| position of the terminal | top |
| Mechanical Design | |
| height | 87.13 mm |
| height with lowest-profile installation | 36.5 mm |
| depth | 35.25 mm |
| length | 87 mm |
| fastening method | TH35 DIN rail |
| net weight | 18.6 g |
| material of the insulating body | Other |
| Environmental conditions | |

ambient temperature during operation

- minimum
- maximum

105 °C
105 °C

Approvals Certificates

General Product Approval

Marine / Shipping



[Confirmation](#)



other

Environment

[Miscellaneous](#)

[Confirmation](#)

[Environmental Con-
firmations](#)

[Environmental Con-
firmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WH2004-0CG07>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8WH2004-0CG07>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH2004-0CG07

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



last modified:

2/8/2023 

