

Conductor connection terminal 16-70mm², f. 5 mm

Powering Business Worldwide™

Part no. AKU70/5
Catalog No. 107189

EL-Nummer 2465027
(Norway)

Delivery program

Product range			60 mm system Compact system
Basic function			Connections
Subrange			Universal conductor connection terminals
Description			With integrated retaining spring, open terminal chamber and captive terminal screw
Terminal area W x H		mm	14 x 14
Width		mm	20.5
Rated operational current	I _e	A	400
conductor			16 - 70 mm ² AWG 4 - AWG 2/0. directly terminated: # 2x (3 x 9 x 0.8 mm) or 6 x 9 x 0.8 mm
For use with			All 5 mm thick flat busbars
Notes			
○ round conductor, solid			
Flexible, round conductor with correctly crimped ferrule			
Round conductor, stranded			
Section conductor, solid			
Sector conductor, stranded			
# CU band			
CU busbar			

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Busbar terminal (EC000001)

Electric engineering, automation, process control engineering / Electrical installation, device / Terminal (not overhead line) / Switch board (ecl@ss10.0.1-27-14-11-46 [BAA025013])

Busbar thickness	mm	5 - 5
Busbar width	mm	0 - 0
Suitable for		Flat rail
Width clamp	mm	20.5
Max. conductor cross section	mm ²	70
Max. rated operation current I _e	A	400
Suitable for round conductor connection		Yes
Suitable for sector conductor connection		Yes
Suitable for strip conductor connection		Yes